

Barn Red Roof Coating F46784

ICP Construction

Version No: **1.2**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **04/20/2017** Print Date: **04/20/2017** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Barn Red Roof Coating F46784
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Roof Coating

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction
Address	150 Dascomb Road Massachusetts Andover United States
Telephone	978-623-9980
Fax	Not Available
Website	Not Available
Email	Not Available

Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Classification

Skin Sensitizer Category 1, Germ cell mutagenicity Category 1B, Carcinogenicity Category 1A, Reproductive Toxicity Category 1B, Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 3

Label elements

GHS label elements





SIGNAL WORD

DANGER

Hazard statement(s)

H317	May cause an allergic skin reaction.
H340	May cause genetic defects.
H350	May cause cancer.
H360	May damage fertility or the unborn child.
H412	Harmful to aquatic life with long lasting effects.

Hazard(s) not otherwise specified

Not Applicable

Chemwatch: 9-388247 Page 2 of 12 Issue Date: 04/20/2017 Version No: 1.2 Print Date: 04/20/2017

Barn Red Roof Coating F46784

P201	Obtain special instructions before use.					
P280	Wear protective gloves/protective clothing/eye protection/face protection.					
P281	Use personal protective equipment as required.					
Precautionary statement(s) Response					
P308+P313	IF exposed or concerned: Get medical advice/attention.					
P363	Wash contaminated clothing before reuse.					

Precautionary statement(s) Storage

P302+P352

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

IF ON SKIN: Wash with plenty of soap and water.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
12251-27-3		nepheline	
7632-00-0	<1	sodium nitrite	
68412-54-4	<1	nonylphenol ethoxylate, branched	
7320-34-5	<1	potassium pyrophosphate	
7664-41-7	<1	ammonia anhydrous liquefied	
330-54-1	<1	diuron	
1332-58-7	<1	<u>kaolin</u>	
10605-21-7	<1	<u>carbendazim</u>	
2425-85-6	1-5	C.I. Pigment Red 3	
1309-37-1	1-5	<u>ferric oxide</u>	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

for diuron:

- ▶ Symptomatic and supportive action is indicated.
- ▶ Methaemoglobinaemia is possible
- if compound is hydrolysed in vivo to aniline.
- Methaemoglobinaemia causes cyanosis. Reversion of methaemoglobin to haemoglobin is spontaneous after removal from exposure, so moderate degrees of cyanosis need be treated only by supportive measures such as bed rest and oxygen inhalation.
- Fig. Thorough cleansing of the entire contaminated area of the body, including the scalp and nails is of the utmost importance.

SECTION 5 FIRE-FIGHTING MEASURES

Chemwatch: 9-388247 Page 3 of 12 Issue Date: 04/20/2017 Version No: 1.2 Print Date: 04/20/2017

Barn Red Roof Coating F46784

Extinguishing media

- ▶ Jets of water.
- ▶ Water spray or fog.
- Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.				
Special protective equipm	ent and precautions for fire-fighters				
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 				
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous fumes. 				

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

May emit corrosive fumes.

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by all means available, spillage from entering drains or water courses. Consider evacuation (or protect in place). No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Contain or absorb spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handlin	Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. DO NOT allow clothing wet with material to stay in contact with skin
Other information	

Chemwatch: 9-388247 Page 4 of 12 Version No: 1.2

Barn Red Roof Coating F46784

Issue Date: 04/20/2017 Print Date: 04/20/2017

Conditions for safe storage, including any incompatibilities

Suitable container

- ► Polyethylene or polypropylene container.
- ▶ Packing as recommended by manufacturer.
- ► Check all containers are clearly labelled and free from leaks.

Storage incompatibility None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ammonia anhydrous liquefied	Ammonia	35 mg/m3 / 50 ppm	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ammonia anhydrous liquefied	Ammonia	25 ppm	35 ppm	Not Available	TLV® Basis: Eye dam; URT irr
US NIOSH Recommended Exposure Limits (RELs)	ammonia anhydrous liquefied	Anhydrous ammonia, Aqua ammonia, Aqueous ammonia [Note: Often used in an aqueous solution.]	18 mg/m3 / 25 ppm	27 mg/m3 / 35 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	diuron	Diuron	10 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
US NIOSH Recommended Exposure Limits (RELs)	diuron	3-(3,4-Dichlorophenyl)-1,1-dimethylurea; Direx®; Karmex®	10 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	kaolin	Kaolin / Kaolin - Respirable fraction	15 mg/m3 / 5 mg/m3	Not Available	Not Available	Total dust;(IGE)
US OSHA Permissible Exposure Levels (PELs) - Table Z3	kaolin	Silicates: Mica / Silicates: Soapstone / Silicates: Talc / Silicates: Tremolite, asbestiforms	0.1 f/cc / 20 mppcf	Not Available	Not Available	(less than 1% crystalline silica) / (containing asbestos) Use asbestos limit;(less than 1% crystalline silica) / (see 29 CFR 1910.1001);(less than 1% crystalline silica)
US ACGIH Threshold Limit Values (TLV)	kaolin	Kaolin	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
US NIOSH Recommended Exposure Limits (RELs)	kaolin	China clay, Clay, Hydrated aluminum silicate, Hydrite, Porcelain clay [Note: Main constituent of Kaolin is Kaolinite (Al2Si2O5(OH)4).]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ferric oxide	Iron oxide fume	10 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ferric oxide	Iron oxide (Fe203)	5 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
US NIOSH Recommended Exposure Limits (RELs)	ferric oxide	Iron(III)oxide, Iron oxide red, Red iron oxide, Red oxide / Ferric oxide, Iron(III) oxide	5 mg/m3	Not Available	Not Available	See Appendix D

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
sodium nitrite	Sodium nitrite	6.4 mg/m3	71 mg/m3	240 mg/m3
nonylphenol ethoxylate, branched	Nonylphenoxypolyethoxyethanol	30 mg/m3	330 mg/m3	2,000 mg/m3
potassium pyrophosphate	Potassium pyrophosphate; (Tetrapotassium diphosphorate)	61 mg/m3	680 mg/m3	1,200 mg/m3
ammonia anhydrous liquefied	Ammonia	Not Available	Not Available	Not Available
ferric oxide	Iron oxide; (Ferric oxide)	15 mg/m3	360 mg/m3	2,200 mg/m3

Ingredient	Original IDLH	Revised IDLH
nepheline	Not Available	Not Available
sodium nitrite	Not Available	Not Available
nonylphenol ethoxylate, branched	Not Available	Not Available
potassium pyrophosphate	Not Available	Not Available
ammonia anhydrous liquefied	500 ppm	300 ppm
diuron	Not Available	Not Available
kaolin	Not Available	Not Available
carbendazim	Not Available	Not Available
C.I. Pigment Red 3	Not Available	Not Available
ferric oxide	N.E. mg/m3 / N.E. ppm	2,500 mg/m3

Chemwatch: 9-388247 Page 5 of 12 Issue Date: 04/20/2017
Version No: 1.2 Print Date: 04/20/2017

Barn Red Roof Coating F46784

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

 $\label{lem:employers} \mbox{Employers may need to use multiple types of controls to prevent employee overexposure.}$

Appropriate engineering controls

- ▶ Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.
- Work should be undertaken in an isolated system such as a "glove-box". Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.
- Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample
 ports or openings closed while the carcinogens are contained within.
- ► Open-vessel systems are prohibited.
- ► Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation
- Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.
- For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.
- ▶ Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).
- Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.
- Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 0.76 m/sec with a minimum of 0.64 m/sec. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.

Personal protection









- Safety glasses with side shields
- Chemical goggles.
- Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC
- ► Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

- ► The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Hands/feet protection

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- Contaminated gloves should be replaced.

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or
 puncture potential
 Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is

recommended.

Body protection

See Other protection below

Other protection

Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]
 Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with

filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715

Chemwatch: 9-388247 Page 6 of 12 Issue Date: 04/20/2017 Version No: 1.2 Print Date: 04/20/2017

Barn Red Roof Coating F46784

or national equivalent] ▶ Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely. Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Frior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood. Overalls. ► P.V.C. apron. ▶ Barrier cream. ► Skin cleansing cream. ► Eye wash unit. Thermal hazards Not Available

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Text		
Physical state	liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Chemwatch: 9-388247

Page 7 of 12 Issue Date: 04/20/2017 Version No: 1.2 Print Date: 04/20/2017 **Barn Red Roof Coating F46784**

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised Eye by tearing or conjunctival redness (as with windburn). Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There is sufficient evidence to suggest that this material directly causes cancer in humans. Based on experiments and other information, there is ample evidence to presume that exposure to this material can cause genetic defects that can be inherited. Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material. Chronic Chronic effects of exposure to diuron may include skin irritation, abnormal pigmentation, growth retardation, blurring of vision, abnormal liver, spleen and thyroid effects; red blood cell destruction, or reduction of the blood's oxygen carrying capacity causing bluish discolouration and breathlessne Benzimidazoles are shown to impair embryonic development and cause genetic abnormalities (often errors in the number of chromosomes). Their activity in the body may also cause cancer and genetic defects by interfering with nucleic acids function. TOXICITY IRRITATION **Barn Red Roof Coating** F46784 Not Available Not Available TOXICITY IRRITATION nepheline Not Available Not Available TOXICITY IRRITATION Inhalation (rat) LC50: 0.0055 mg/L/4hr^[2] Eye (rabbit): 500 mg/24hr - mild sodium nitrite Oral (rat) LD50: 157.9 mg/kg^[2] TOXICITY IRRITATION nonylphenol ethoxylate, Dermal (rabbit) LD50: 2640 mg/kg^[1] Eye: Severe branched Oral (rat) LD50: >15 mg/kg^[1] Skin : Severe TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg^[1] Not Available potassium pyrophosphate Oral (rat) LD50: >300-<2000 mg/kg>[1] TOXICITY IRRITATION dermal (rat) LD50: 4.84 mg/L^[2] Not Available ammonia anhydrous Inhalation (rat) LC50: 2000 ppm/4hr^[2] liquefied Inhalation (rat) LC50: 9500 ppm/1hr^[2] Oral (rat) LD50: 350 mg/kg^[1] TOXICITY IRRITATION dermal (rat) LD50: >5000 mg/kg^[2] Not Available diuron Oral (rat) LD50: 1000 mg/kg^[2] TOXICITY IRRITATION Not Available Not Available TOXICITY IRRITATION dermal (rat) LD50: 2000 mg/kg^[2] Eye (rabbit): non-irritating * carbendazim Oral (rat) LD50: 6400 mg/kg^[2] Skin (rabbit): non-irritating * TOXICITY IRRITATION Oral (rat) LD50: >5000 mg/kg^[2] C.I. Pigment Red 3 Eye (human): non irritant Skin (human): non irritant TOXICITY IRRITATION ferric oxide Oral (rat) LD50: >5000 mg/kg^[1] Not Available 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data Legend: extracted from RTECS - Register of Toxic Effect of chemical Substances

Chemwatch: 9-388247 Page 8 of 12 Issue Date: 04/20/2017 Version No: 1.2 Print Date: 04/20/2017

Barn Red Roof Coating F46784

MEDLIEUNE	No data ausilable No data ausilabla
NEPHELINE	No data available No data available
SODIUM NITRITE	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis Tumorigenic - Carcinogenic by RTECS criteria.
NONYLPHENOL ETHOXYLATE, BRANCHED	Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products. Exposure to these chemicals can occur through ingestion, inhalation, or contact with the skin or eyes. Studies of acute toxicity show that volumes well above a reasonable intake level would have to occur to produce any toxic response. Both laboratory and animal testing has shown that there is no evidence for alcohol ethoxylates (AEs) causing genetic damage, mutations or cancer. No advers reproductive or developmental effects were observed. Tri-ethylene glycol ethers undergo enzymatic oxidation to toxic alkoxy acids. They may irritate the skin and the eyes. At high oral doses, they may cause depressed reflexes, flaccid muscle tone, breathing difficulty and coma.
POTASSIUM PYROPHOSPHATE	No data available. Data for sodium analogue only. tetrasodium pyrophosphate
DIURON	Diuron is absorbed readily through the gut and lungs while uptake through the skin is more limited. It is slightly toxic to mammals but juveniles are more susceptible than adults(18). The oral LD50 in rats is 3-4 g/kg and the dermal LD50 is > 2 g/kg(19). Note: Equivocal animal tumorigenic agent by RTECS criteria. NOTE: This substance may contain impurities (tetrachlorazobenzene and tetrachloroazoxybenzene). Maximum impurity levels are proscribed under various jurisdictions ADI: 0.006 mg/kg/day NOEL: 0.625 mg/kg/day
KAOLIN	for bentonite clays: Bentonite (CAS No. 1302-78-9) consists of a group of clays formed by crystallisation of vitreous volcanic ashes that were deposited in water. The expected acute oral toxicity of bentonite in humans is very low (LD50>15 g/kg). However, severe anterior segment inflammation, uveitis and retrocorneal abscess from eye exposure were reported when bentonite had been used as a prophypaste.
CARBENDAZIM	Benomyl (a precursor of carbendazim) sensitises skin in humans. Benomyl and carbendazim represent a very low risk for acute poisoning in humans. Carbendazim has low acute toxicity and is excretedin the urine. [* The Pesticides Manual, Incorporating The Agrochemicals Handbook, 10th Edition, Editor Clive Tomlin, 1994, British Crop Protection Council] Intraperitoneal (Rat, adult male) LD50: 7320 mg/kg * Intraperitoneal (Rat, adult female) LD50: 15000 mg/kg * Inhalation LC50 (4 h) for rats, rabbits, guinea pigs or cats no effect with suspension (10 g/l water). * NOEL (2 y) for dogs 300 mg/kg diet, corresponding to 6-7 mg/kg b.w. ADI 0.01 mg/kg b.w. * Toxicity Class WHO III; EPA IV
C.I. PIGMENT RED 3	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Detailed analysis of molecular structure indicates that the azo colourant can split off cancer-causing arylamines. The azo linkage, a double bond between two nitrogen atoms, is considered the most unstable part of an azo dye. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. Bacterial mutagen Subchronic or Prechronic Exposure: Treatment of F344 rats and B6C3F1 mice with C.I. Pigment Red 3 in the diet (10, 5.0, 2.5, 1.25, 0.6 or 0.3%) for 14 and 90 days resulted in haematological alterations consistent with haemolytic anemia. Rats appeared to be more sensitive than mice to the haematological effects. Long-term dietary administration resulted in the development of tumours of the liver, skin, adrenals and Zymbal gland in rats and kidney and thyroid tumors in mice. An Ames bacterial test has given evidence of weak mutagenicity, but no chromosome effects were seen in mammalian cells in culture. [Under the conditions of a 2 yr feed study, there was some evidence of carcinogenic activity of C.I. Pigment Red 3 in male F344/N rats as exhibited by increased insidences of hearing and phase partners of the admentation of the conditions of the partners of the admentation of the conditions of the partners of the admentation of the conditions of the partners of the admentation of the conditions of the partners of the

POTASSIUM PYROPHOSPHATE & AMMONIA ANHYDROUS LIQUEFIED & FERRIC OXIDE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.

increased incidences of benign pheochromocytomas of the adrenal gland. The marginal increase in the incidences of squamous cell papillomas of the skin and

AMMONIA ANHYDROUS LIQUEFIED & DIURON & KAOLIN

No significant acute toxicological data identified in literature search.

Zymbals gland carcinomas may have been related to C.I.

Acute Toxicity	0	Carcinogenicity	~
Skin Irritation/Corrosion	0	Reproductivity	✓
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	0
Mutagenicity	✓	Aspiration Hazard	0

Legend:

X - Data available but does not fill the criteria for classification

✓ – Data available to make classification

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

•					
Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
sodium nitrite	LC50	96	Fish	0.048mg/L	4
sodium nitrite	EC50	48	Crustacea	ca.12.5100mg/L	1
sodium nitrite	EC50	96	Algae or other aquatic plants	12.537mg/L	3
sodium nitrite	EC50	216	Crustacea	1.8mg/L	4
sodium nitrite	NOEC	2	Fish	0.02mg/L	4
nonylphenol ethoxylate, branched	LC50	96	Fish	0.136mg/L	2

Chemwatch: 9-388247 Page 9 of 12 Issue Date: 04/20/2017 Version No: 1.2 Print Date: 04/20/2017

Barn Red Roof Coating F46784

nonylphenol ethoxylate, branched	NOEC	2184	Fish	ca.0.006mg/L	2
ammonia anhydrous liquefied	LC50	96	Fish	0.068mg/L	2
ammonia anhydrous liquefied	EC50	48	Crustacea	0.179mg/L	5
ammonia anhydrous liquefied	EC50	96	Algae or other aquatic plants	311.661mg/L	3
ammonia anhydrous liquefied	EC50	1440	Crustacea	0.016mg/L	5
ammonia anhydrous liquefied	NOEC	Not Applicable	Fish	0.0015mg/L	5
diuron	LC50	96	Fish	0.5mg/L	4
diuron	EC50	48	Crustacea	1.4mg/L	1
diuron	EC50	72	Algae or other aquatic plants	0.00055mg/L	4
diuron	BCF	792	Algae or other aquatic plants	0.159mg/L	4
diuron	EC50	336	Algae or other aquatic plants	0.00035mg/L	4
diuron	NOEC	336	Algae or other aquatic plants	0.0000005mg/L	4
carbendazim	LC50	96	Fish	0.007mg/L	4
carbendazim	EC50	48	Crustacea	0.02mg/L	4
carbendazim	EC50	96	Algae or other aquatic plants	3.945mg/L	3
carbendazim	EC50	24	Crustacea	0.0035mg/L	4
carbendazim	NOEC	480	Crustacea	<0.0031mg/L	4
C.I. Pigment Red 3	LC50	96	Fish	0.082mg/L	3
C.I. Pigment Red 3	EC50	96	Algae or other aquatic plants	0.018mg/L	3
C.I. Pigment Red 3	NOEC	72	Algae or other aquatic plants	>0.006mg/L	2
erric oxide	LC50	96	Fish	0.05mg/L	2
erric oxide	EC50	72	Algae or other aquatic plants	18mg/L	2
erric oxide	EC50	504	Crustacea	4.49mg/L	2
ferric oxide	NOEC	504	Fish	0.52mg/L	2
Legend:	(QSAR) - Aquatic To		Registered Substances - Ecotoxicological Info Ecotox database - Aquatic Toxicity Data 5. EC ncentration Data 8. Vendor Data		

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Diuron: Vapor pressure: 6.90 x10-8 mm Hg (25 C); Henry's law constant: 5.10 x 10-10 atm m3 mol-1.

Atmospheric Fate: Diuron is non-volatile in the atmosphere and is unlikely to be dispersed over large areas. Diuron has a low tendency to volatilize from water or moist soils. Volatilization is insignificant except when diuron is exposed on the soil surface for several days or weeks under hot, dry conditions. Photolysis is generally not a principal route of diuron degradation in aqueous systems

Terrestrial Fate: Soil - Microbial degradation is the primary means of diuron dissipation from soil. Tetrachloroazobenzene (TCAB) and tetrachloroazoxybenzene (TCAOB) sorb very strongly to soils and are not likely to leach. Diuron leaching is greatest in soils low in organic matter and soils with high permeability to water, such as coarse soils. Diuron is moderately to highly persistent in soils. The average field half-life is 90 days; however, half-lives are highly variable. Photodegradation is not considered a primary dissipation route, but losses can be significant if diuron remains on the soil surface for several days or weeks. Diuron is mobile in soil and has a relatively low tendency to sorb to soils and sediments. Plants - Residues, at levels toxic to plants, generally dissipate within a season when applied at low selective rates. At higher application rates, residues may persist for more than one year. Diuron is readily absorbed through the root system of plants and less readily through the leaves and stems. Diuron inhibits plant photosynthesis.

Aquatic Fate: Photolysis is not a principal route for degradation in aqueous systems. Diuron is both mobile and relatively persistent in aqueous systems, and is prone to off-site movement in surface runoff and migration to ground water. Microbes are the primary agents in the degradation of diuron in aquatic environments. Reductive dechlorination of the product has been observed in anaerobic pond sediments.

Ecotoxicity: Diuron is slightly toxic to bobwhite quail and practically nontoxic to mallard duck. Diuron is also slightly toxic to bluegill sunfish and moderately toxic to rainbow trout and sheepshead minnow. Diuron is highly toxic to Daphnia magna water fleas but not acutely toxic to honey bees. Diuron has been attributed to unnatural shell thickening in the Pacific oyster. Little tissue storage in mammals is anticipated. Diuron is toxic to fish and aquatic invertebrates.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
sodium nitrite	LOW	LOW
ammonia anhydrous liquefied	LOW	LOW
diuron	HIGH	HIGH
carbendazim	HIGH	HIGH
C.I. Pigment Red 3	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
sodium nitrite	LOW (LogKOW = 0.0564)
ammonia anhydrous liquefied	LOW (LogKOW = 0.229)
diuron	LOW (BCF = 14)

Barn Red Roof Coating F46784

carbendazim	LOW (BCF = 3.5)
C.I. Pigment Red 3	LOW (BCF = 2.9)

Mobility in soil

Ingredient	Mobility
sodium nitrite	LOW (KOC = 23.74)
ammonia anhydrous liquefied	LOW (KOC = 14.3)
diuron	LOW (KOC = 136)
carbendazim	LOW (KOC = 175.8)
C.I. Pigment Red 3	LOW (KOC = 69830)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- ▶ Recycling
- Product / Packaging disposal
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

NEPHELINE(12251-27-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

SODIUM NITRITE(7632-00-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US CWA (Clean Water Act) - List of Hazardous Substances
Monographs	US EPCRA Section 313 Chemical List
US - Massachusetts - Right To Know Listed Chemicals	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Pennsylvania - Hazardous Substance List	

NONYLPHENOL ETHOXYLATE, BRANCHED(68412-54-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

POTASSIUM PYROPHOSPHATE(7320-34-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemwatch: 9-388247 Page 11 of 12 Issue Date: 04/20/2017 Version No. 1.2 Print Date: 04/20/2017

Barn Red Roof Coating F46784

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

AMMONIA ANHYDROUS LIQUEFIED(7664-41-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft

US - Alaska Limits for Air Contaminants

US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)

US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)

US - California Permissible Exposure Limits for Chemical Contaminants

US - Hawaii Air Contaminant Limits

US - Idaho - Limits for Air Contaminants

US - Massachusetts - Right To Know Listed Chemicals

US - Michigan Exposure Limits for Air Contaminants

US - Minnesota Permissible Exposure Limits (PELs)

US - Oregon Permissible Exposure Limits (Z-1)

US - Pennsylvania - Hazardous Substance List US - Rhode Island Hazardous Substance List

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air

Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US ACGIH Threshold Limit Values (TLV)

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US CWA (Clean Water Act) - List of Hazardous Substances

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US SARA Section 302 Extremely Hazardous Substances

US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

DIURON(330-54-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants

US - California Permissible Exposure Limits for Chemical Contaminants

US - California Proposition 65 - Carcinogens

US - Hawaii Air Contaminant Limits

US - Massachusetts - Right To Know Listed Chemicals

US - Michigan Exposure Limits for Air Contaminants

US - Minnesota Permissible Exposure Limits (PELs)

US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air

Contaminants

US - Washington Permissible exposure limits of air contaminants

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US CWA (Clean Water Act) - List of Hazardous Substances

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk

Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

KAOLIN(1332-58-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants

US - California Permissible Exposure Limits for Chemical Contaminants

US - Hawaii Air Contaminant Limits

US - Idaho - Limits for Air Contaminants

US - Michigan Exposure Limits for Air Contaminants

US - Minnesota Permissible Exposure Limits (PELs) US - Oregon Permissible Exposure Limits (Z-1)

US - Pennsylvania - Hazardous Substance List

US - Rhode Island Hazardous Substance List

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US OSHA Permissible Exposure Levels (PELs) - Table Z3 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

CARBENDAZIM(10605-21-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

C.I. PIGMENT RED 3(2425-85-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

FERRIC OXIDE(1309-37-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US - Alaska Limits for Air Contaminants

US - California Permissible Exposure Limits for Chemical Contaminants

US - Hawaii Air Contaminant Limits US - Idaho - Limits for Air Contaminants

US - Massachusetts - Right To Know Listed Chemicals

US - Michigan Exposure Limits for Air Contaminants

US - Minnesota Permissible Exposure Limits (PELs)

US - Oregon Permissible Exposure Limits (Z-1)

US - Pennsylvania - Hazardous Substance List US - Rhode Island Hazardous Substance List

US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants

US - Washington Permissible exposure limits of air contaminants

US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Levels (PELs) - Table Z1 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Immediate (acute) health hazard	Yes
Delayed (chronic) health hazard	Yes
Fire hazard	No
Pressure hazard	No

Barn Red Roof Coating F46784

No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Sodium nitrite	100	45.4
Ammonia	100	45.4
Diuron	100	45.4
Carbamic acid, 1H-benzimidazol-2-yl, methyl ester	10	4.54

State Regulations

Reactivity hazard

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

\parallel US - CALIFORNIA PREPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Diuron Listed

National Inventory	Status
Australia - AICS	N (nepheline)
Canada - DSL	Υ
Canada - NDSL	N (kaolin; nepheline; diuron; carbendazim; sodium nitrite; ammonia anhydrous liquefied; potassium pyrophosphate; ferric oxide; C.I. Pigment Red 3; nonylphenol ethoxylate, branched)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	N (nepheline)
Japan - ENCS	N (kaolin; nepheline; nonylphenol ethoxylate, branched)
Korea - KECI	Y
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	N (nepheline)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

Ingredients with multiple cas numbers

Name	CAS No
nepheline	12251-27-3, 37244-96-5
C.I. Pigment Red 3	2425-85-6, 12238-48-1, 12240-01-6, 39310-30-0, 78690-69-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.