

Elastomeric Coating - F581 Series

Product Description

Elastomeric Coating a high quality exterior formulated to fill and bridge small imperfections and pinholes in masonry block and porous concrete. This product fill voids and prevent seepage from driving rains and snow. This Elastomeric coating is easy to apply, alkali resistant and provides a uniform surface on its own and is capable of receiving latex finish coats. It is not water sensitive after application and its inherent flexibility gives it the finest characteristics available in an elastomeric coatings today

Recommended Use

Block, cementitious surfaces

General Surface Preparation

Application

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Precautions

Environmental Health and Safety Information

Elastomeric Coating - F581 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Notes

Technical Data

Product Type	Finish
Exposure	Exterior
Specular Gloss	12° ± 5
Volume Solids	
Weight Solids	
Vehicle Solids	
Pigment	
Wet Film Thickness	
Dry Film Thickness	
Viscosity @ 77 °F	
Max VOC	
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	
Porous	
<i>(Spray Application is 50% of above)</i>	

Drying Times

To Touch	
To Handle	
To Recoat	
To Wash	
<i>(@ 70 - 77 °F, 50% R.H)</i>	

Surface Temperature At Application

Maximum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	
Roller	
Airless Spray	

Available Package Sizes

5 Gallon	Gallon
<i>(Weight Per Gallon: lbs. ± .5 lb)</i>	

Available Colors and Bases

Available in 0 stock colors