

Vogue Theatrical Paint Burnt Sienna - F000V38

ICP Construction

Version No: **3.3**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **09/25/2018** Print Date: **09/25/2018** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Vogue Theatrical Paint Burnt Sienna - F000V38
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Theatrical Paint
--------------------------	------------------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction
Address	150 Dascomb Road Andover MA United States
Telephone	978-623-9980
Fax	Not Available
Website	http://www.icp-construction.com/
Email	Not Available

Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Carcinogenicity Category 1A, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)

Label elements

Hazard pictogram(s)







SIGNAL WORD DANGER

Hazard statement(s)

• •	
H315	Causes skin irritation.
H318	Causes serious eye damage.
H350	May cause cancer.
H335	May cause respiratory irritation.

Version No: 3.3

Vogue Theatrical Paint Burnt Sienna - F000V38

Print Date: 09/25/2018

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P271	Use only outdoors or in a well-ventilated area.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1309-37-1	6.85	<u>ferric oxide</u>
1333-86-4	<1	carbon black
471-34-1	1-5	<u>calcium carbonate</u>
12001-26-2	2.05-2.28	<u>mica</u>
68476-25-5	<1	<u>feldspars</u>
1317-65-3	7-12	limestone
14807-96-6	9.14	talc

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

See Section 11

 Chemwatch: 9-590216
 Page 3 of 11
 Issue Date

 Version No: 3.3
 Print Date
 Print Date

Vogue Theatrical Paint Burnt Sienna - F000V38

Issue Date: **09/25/2018**Print Date: **09/25/2018**

For acute or short term repeated exposures to iron and its derivatives:

- Always treat symptoms rather than history.
- In general, however, toxic doses exceed 20 mg/kg of ingested material (as elemental iron) with lethal doses exceeding 180 mg/kg.
- Control of iron stores depend on variation in absorption rather than excretion. Absorption occurs through aspiration, ingestion and burned skin.
- ▶ Hepatic damage may progress to failure with hypoprothrombinaemia and hypoglycaemia. Hepatorenal syndrome may occur.
- Iron intoxication may also result in decreased cardiac output and increased cardiac pooling which subsequently produces hypotension.
- Serum iron should be analysed in symptomatic patients. Serum iron levels (2-4 hrs post-ingestion) greater that 100 ug/dL indicate poisoning with levels, in excess of 350 ug/dL, being potentially serious. Emesis or lavage (for obtunded patients with no gag reflex) are the usual means of decontamination.
- Activated charcoal does not effectively bind iron.
- Catharsis (using sodium sulfate or magnesium sulfate) may only be used if the patient already has diarrhoea.
- Deferoxamine is a specific chelator of ferric (3+) iron and is currently the antidote of choice. It should be administered parenterally. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.	
Special protective equipment	and precautions for fire-fighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. 	
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous fumes. May emit corrosive fumes. 	

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.
Major Spills	Moderate hazard. ▶ Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling Safe handling Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Do Not allow clothing wet with material to stay in contact with skin

Conditions for safe storage,	including any incompatibilities
Suitable container	Polyethylene or polypropylene container. Packing as recommended by manufacturer.
Storage incompatibility	For iron oxide (ferric oxide): Avoid storage with aluminium, calcium hypochlorite and ethylene oxide. Risk of explosion occurs following reaction with powdered aluminium, calcium silicide, ethylene oxide (polymerises), carbon monoxide, magnesium and perchlorates. WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive. Acetic acid: vapours forms explosive mixtures with air (above 39 C.) reacts violently with bases such as carbonates and hydroxides (giving off large quantities of heat), oxidisers, organic amines, acetaldehyde, potassium tert-butoxide reacts (sometimes violently), with strong acids, aliphatic amines, alkanolamines, alkylene oxides, epichlorohydrin, acetic anhydride, 2-aminoethanol, ammonia, ammonium nitrate, bromine pentafluoride, chlorosulfonic acid, chromic acid, chromium trioxide, ethylenediamine, ethylenemine, hydrogen peroxide, isocyanates, oleum, perchloric acid, permanganates, phosphorus isocyanate, phosphorus trichloride, sodium peroxide, xylene attacks cast iron, stainless steel and other metals, forming flammable hydrogen gas attacks many forms of rubber, plastics and coatings

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Version No: 3.3

Issue Date: 09/25/2018 Print Date: 09/25/2018 Vogue Theatrical Paint Burnt Sienna - F000V38

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ferric oxide	Ferric oxide, Iron(III) oxide	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ferric oxide	Iron(III)oxide, Iron oxide red, Red iron oxide, Red oxide	Not Available	Not Available	Not Available	See Appendix D
US ACGIH Threshold Limit Values (TLV)	ferric oxide	Iron oxide (Fe203)	5 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ferric oxide	Iron oxide fume	10 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ferric oxide	Rouge: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ferric oxide	Rouge: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Acetylene black, Channel black, Furnace black, Lamp black, Thermal black	3.5 mg/m3	Not Available	Not Available	Ca See Appendix A See Appendix C
US ACGIH Threshold Limit Values (TLV)	carbon black	Carbon black	3 mg/m3	Not Available	Not Available	TLV® Basis: Bronchitis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Calcium carbonate, Natural calcium carbonate [Note: Marble is a metamorphic form of calcium carbonate.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Calcium carbonate, Natural calcium carbonate [Note: Calcite & aragonite are commercially important natural calcium carbonates.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	calcium carbonate	Calcium salt of carbonic acid [Note: Occurs in nature as as limestone, chalk, marble, dolomite, aragonite, calcite and oyster shells.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	calcium carbonate	Marble: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	calcium carbonate	Limestone: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	calcium carbonate	Limestone: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	calcium carbonate	Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	calcium carbonate	Calcium carbonate: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	calcium carbonate	Marble: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	mica	Biotite, Lepidolite, Margarite, Muscovite, Phlogopite, Roscoelite, Zimmwaldite	3 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z3	mica	Silicates: Mica	20 mppcf	Not Available	Not Available	(Name ((less than 1% crystalline silica)))
US ACGIH Threshold Limit Values (TLV)	mica	Mica	3 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	mica	Silicates (less than 1% crystalline silica): Mica (respirable dust)	Not Available	Not Available	Not Available	See Table Z-3
US NIOSH Recommended Exposure Limits (RELs)	limestone	Calcium carbonate, Natural calcium carbonate [Note: Calcite & aragonite are commercially important natural calcium carbonates.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	limestone	Calcium carbonate, Natural calcium carbonate [Note: Marble is a metamorphic form of calcium carbonate.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	limestone	Calcium salt of carbonic acid [Note: Occurs in nature as as limestone, chalk, marble, dolomite, aragonite, calcite and oyster shells.]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Calcium carbonate: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Limestone: Total dust	15 mg/m3	Not Available	Not Available	Not Available

Chemwatch: 9-590216 Page 5 of 11 Issue Date: 09/25/2018 Version No: 3.3 Print Date: 09/25/2018

Vogue Theatrical Paint Burnt Sienna - F000V38

US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Limestone: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Marble: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Marble: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	limestone	Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	talc	Massive talc, Soapstone silicate, Steatite	6 (total), 3 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	talc	Hydrous magnesium silicate, Steatite talc	2 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Talc	Not Available	Not Available	Not Available	(Name ((less than 1% crystalline silica); (containing asbestos) Use asbestos limit))
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Talc	20 mppcf	Not Available	Not Available	(Name ((less than 1% crystalline silica); (not containing asbestos))); (TWA mppcf (((c) Containing less than 1% quartz; if 1% quartz or more, use quartz limit.)))
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Soapstone	20 mppcf	Not Available	Not Available	(Name ((less than 1% crystalline silica)))
US ACGIH Threshold Limit Values (TLV)	talc	Talc - Containing no asbestos fibers	2 mg/m3	Not Available	Not Available	TLV® Basis: Pulm fibrosis; pulm func
US ACGIH Threshold Limit Values (TLV)	talc	Talc - Containing asbestos fibers	Not Available	Not Available	Not Available	TLV® Basis: Use Asbestos TLV®
US OSHA Permissible Exposure Levels (PELs) - Table Z1	talc	Silicates (less than 1% crystalline silica): Talc (containing asbestos); use asbestos limit	Not Available	Not Available	Not Available	see 29 CFR 1910.1001; See Table Z-3
US OSHA Permissible Exposure Levels (PELs) - Table Z1	talc	Silicates (less than 1% crystalline silica): Talc (containing no asbestos), respirable dust	Not Available	Not Available	Not Available	See Table Z-3

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ferric oxide	Iron oxide; (Ferric oxide)	15 mg/m3	360 mg/m3	2,200 mg/m3
carbon black	Carbon black	9 mg/m3	99 mg/m3	590 mg/m3
calcium carbonate	Limestone; (Calcium carbonate; Dolomite)	45 mg/m3	500 mg/m3	3,000 mg/m3
calcium carbonate	Carbonic acid, calcium salt	45 mg/m3	210 mg/m3	1,300 mg/m3
mica	Mica; (mica silicates)	9 mg/m3	99 mg/m3	590 mg/m3
limestone	Limestone; (Calcium carbonate; Dolomite)	45 mg/m3	500 mg/m3	3,000 mg/m3
limestone	Carbonic acid, calcium salt	45 mg/m3	210 mg/m3	1,300 mg/m3
talc	Talc	6 mg/m3	66 mg/m3	400 mg/m3

Ingredient	Original IDLH	Revised IDLH
ferric oxide	2,500 mg/m3	Not Available
carbon black	1,750 mg/m3	Not Available
calcium carbonate	Not Available	Not Available
mica	1,500 mg/m3	Not Available
feldspars	Not Available	Not Available
limestone	Not Available	Not Available
talc	1,000 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Personal protection









Eye and face protection

Safety glasses with side shields. ► Chemical goggles.

Skin protection

See Hand protection below

▶ Wear chemical protective gloves, e.g. PVC.

▶ Wear safety footwear or safety gumboots, e.g. Rubber

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Body protection

See Other protection below

Page 6 of 11

Vogue Theatrical Paint Burnt Sienna - F000V38

Issue Date: **09/25/2018** Print Date: **09/25/2018**

Other protection

Overalls.

▶ P.V.C.

Respiratory protection

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	If applied to the eyes, this material causes severe eye damage.
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Chronic excessive intake of iron have been associated with damage to the liver and pancreas. People with a genetic disposition to poor control over iron are at an increased risk. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Vogue Theatrical Paint Burnt	
Sienna - F000V38	

TOXICITY	IRRITATION
Not Available	Not Available

Chemwatch: 9-590216 Page 7 of 11 Issue Date: 09/25/2018
Version No: 3.3 Print Date: 09/25/2018

Vogue Theatrical Paint Burnt Sienna - F000V38

TOXICITY IRRITATION ferric oxide Oral (rat) LD50: >5000 mg/kg^[1] Not Available TOXICITY IRRITATION Dermal (rabbit) LD50: >3000 mg/kg^[2] Not Available carbon black Oral (rat) LD50: >10000 mg/kg^[1] TOXICITY IRRITATION calcium carbonate dermal (rat) LD50: >2000 mg/kg^[1] Eye (rabbit): 0.75 mg/24h - SEVERE Oral (rat) LD50: >2000 mg/kg^[1] Skin (rabbit): 500 mg/24h-moderate TOXICITY IRRITATION Not Available Not Available TOXICITY IRRITATION feldspars Not Available Not Available TOXICITY IRRITATION limestone Oral (rat) LD50: 6450 mg/kg^[2] Skin (rabbit): 500 mg/24h-moderate TOXICITY IRRITATION talc Not Available Skin (human): 0.3 mg/3d-I mild 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified Leaend: data extracted from RTECS - Register of Toxic Effect of chemical Substances **CARBON BLACK** WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported LIMESTONE Eye (rabbit) 0.75: mg/24h -The overuse of talc in nursing infants has resulted in respiratory damage causing fluid in the lungs and lung inflammation which may lead to death within hours of inhalation. Long-term exposure can also cause a variety of respiratory symptoms. TALC The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. Vogue Theatrical Paint Burnt Sienna - F000V38 & FERRIC Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as **OXIDE & CALCIUM** reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. **CARBONATE & TALC CARBON BLACK & MICA &** No significant acute toxicological data identified in literature search. FELDSPARS & TALC The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis **CALCIUM CARBONATE &** The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, LIMESTONE scaling and thickening of the skin. No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects 0 Carcinogenicity **Acute Toxicity** Skin Irritation/Corrosion Reproductivity Serious Eve Damage/Irritation STOT - Single Exposure Respiratory or Skin 0 STOT - Repeated Exposure 0 sensitisation Mutagenicity 0 **Aspiration Hazard** 0

Legend:

X − Data available but does not fill the criteria for classification
Pote available to make classification

Data available to make classification

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Chemwatch: 9-590216 Version No: 3.3 Page 8 of 11

Vogue Theatrical Paint Burnt Sienna - F000V38

Issue Date: **09/25/2018**Print Date: **09/25/2018**

gue Theatrical Paint Burnt	ENDPOINT TEST DURATION (HR)			SPECIES		VALUE		SOURCE		
Sienna - F000V38	Not Available	Not Available Not Available			Not Available N		Not Available		Not Available	
	ENDPOINT	TE	ST DUDATION (UD)	SPEC	IES			VALUE		SOURCE
	LC50	TEST DURATION (HR) 96		Fish	iLO					2
ferric oxide	EC50	72			or other aquatic pla	inte		0.05mg/L 18mg/L		2
	NOEC	504	1	Fish	or other aquatic pra	iiito		0.52mg/L		2
	ENDPOINT		TEST DURATION (HR)		SPECIES		VALUE		sou	JRCE
carbon black	LC50		96		Fish		=1000m	g/L	1	
	NOEC		96		Fish		=1000m	g/L	1	
calcium carbonate										
	ENDPOINT	TEST DURATION (HR)		SPECIES		VALUE			SOURCE	
	LC50	96		Fish			>56000mg/L 4		4	
	EC50	72		Algae or other aquatic plants			:	>14mg/L 2		2
	NOEC	72		Algae or other aquatic plants			14mg/L 2			
	ENDPOINT		TEST DURATION (HR)		SPECIES	V	ALUE		SOUR	CE
mica	Not Available Not Available		Not Available			Not Available		Not Available		
					222022				00115	
feldspars	ENDPOINT	,		SPECIES			VALUE		SOURCE	
	Not Available		Not Available Not Available Not A			ot Availab	t Available Not Available			
	ENDPOINT	TES	ST DURATION (HR)	SPECIES			VALUE			SOURCE
	LC50	96		Fish			>56000mg			4
limestone	EC50	72		Algae or other aquatic plants			:	>14mg/L		2
	NOEC	72		Algae or	Algae or other aquatic plants			14mg/L		2
	ENDPOINT		TEST DURATION (HR)		SPECIES	V	ALUE		SOUR	CF
talc	Not Available		Not Available	Not Available			Not Available		Not Available	

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

▶ DO NOT allow wash water from cleaning or process equipment to enter drains.

- It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

Version No: 3.3 Vogue Theatrical Paint Burnt Sienna - F000V38

Issue Date: **09/25/2018**Print Date: **09/25/2018**

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

FERRIC OXIDE(1309-37-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV)
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - Oregon Permissible Exposure Limits (Z-1)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Rhode Island Hazardous Substance List	US TSCA Chemical Substance Inventory - Interim List of Active Substances

CARBON BLACK(1333-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Rhode Island Hazardous Substance List
Monographs	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Proposition 65 - Carcinogens	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV)
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL):	US OSHA Permissible Exposure Levels (PELs) - Table Z1
Carcinogens	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Oregon Permissible Exposure Limits (Z-1)	US TSCA Chemical Substance Inventory - Interim List of Active Substances

CALCIUM CARBONATE(471-34-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Massachusetts - Right To Know Listed Chemicals	Contaminants
US - Michigan Exposure Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
	US TSCA Chemical Substance Inventory - Interim List of Active Substances

MICA(12001-26-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List

US - Alaska Limits for Air Contaminants	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - Hawaii Air Contaminant Limits	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Idaho - Limits for Air Contaminants	Contaminants
US - Idaho - Toxic and Hazardous Substances - Mineral Dust	US - Washington Permissible exposure limits of air contaminants
US - Massachusetts - Right To Know Listed Chemicals	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Michigan Exposure Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z-3 Mineral Dusts
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV)
US - Oregon Permissible Exposure Limits (Z-3)	US NIOSH Recommended Exposure Limits (RELs)
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z3

FELDSPARS(68476-25-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemwatch: 9-590216 Page 10 of 11 Issue Date: 09/25/2018 Version No: 3.3 Print Date: 09/25/2018

Vogue Theatrical Paint Burnt Sienna - F000V38

US - Idaho - Limits for Air Contaminants US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air US TSCA Chemical Substance Inventory - Interim List of Active Substances Contaminants US - Washington Permissible exposure limits of air contaminants LIMESTONE(1317-65-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS US - Alaska Limits for Air Contaminants US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants US - Hawaii Air Contaminant Limits US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants US - Idaho - Limits for Air Contaminants US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants US - Massachusetts - Right To Know Listed Chemicals US - Michigan Exposure Limits for Air Contaminants US - Washington Permissible exposure limits of air contaminants US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants US - Minnesota Permissible Exposure Limits (PELs) US NIOSH Recommended Exposure Limits (RELs) US - Oregon Permissible Exposure Limits (Z-1) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US - Pennsylvania - Hazardous Substance List US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US - Rhode Island Hazardous Substance List

TALC(14807-96-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

TALO(14007-30-0) TO TOOME ON THE TOLLOWING REGULATORY EIGHT	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for A
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits fo
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - California Proposition 65 - Carcinogens	US - Washington Permissible exposure limits of air contaminants
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Conta
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z-3 Mineral Dusts
US - Idaho - Toxic and Hazardous Substances - Mineral Dust	US ACGIH Threshold Limit Values (TLV)
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US NIOSH Recommended Exposure Limits (RELs)
US - Minnesota Permissible Exposure Limits (PELs)	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL):	US OSHA Permissible Exposure Levels (PELs) - Table Z3
Carcinogens	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Oregon Permissible Exposure Limits (Z-3)	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Pennsylvania - Hazardous Substance List	
110 01 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	

US TSCA Chemical Substance Inventory - Interim List of Active Substances

ure Limits Table Z-1-A Final Rule Limits for Air Contaminants

ure Limits Table Z-1-A Transitional Limits for Air

ous Substances Table Z1 Limits for Air Contaminants

US - Rhode Island Hazardous Substance List

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

Chemwatch: 9-590216 Page 11 of 11 Issue Date: 09/25/2018

Vogue Theatrical Paint Burnt Sienna - F000V38

Version No: 3.3 Print Date: 09/25/2018

Carbon black (airborne, unbound particles of respirable size), Talc containing asbestiform fibers Listed

National Inventory Status

National Inventory	Status
Australia - AICS	Y
Canada - DSL	N (feldspars)
Canada - NDSL	N (talc; ferric oxide; carbon black; mica)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	N (mica)
Japan - ENCS	N (feldspars; mica)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	N (mica)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	09/25/2018
Initial Date	09/26/2018

CONTACT POINT

Other information

Ingredients with multiple cas numbers

Name	CAS No
calcium carbonate	471-34-1, 13397-26-7, 15634-14-7, 1317-65-3, 72608-12-9, 878759-26-3, 63660-97-9, 459411-10-0, 198352-33-9, 146358-95-4
mica	12001-26-2, 129899-84-9, 61076-94-6
feldspars	68476-25-5, 12244-10-9

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

^{**}PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES**