

Everlife Waterborne Paint Satin Sandstone - F10067

ICP Construction

Version No: **3.3**Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **05/02/2018** Print Date: **05/15/2018** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Everlife Waterborne Paint Satin Sandstone - F10067
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses Interior/Exterior Paint

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction
Address	150 Dascomb Road MA 01810 United States
Telephone	978-623-9980
Fax	Not Available
Website	https://www.icp-construction.com/
Email	Not Available

Emergency phone number

3, .	
Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Eye Irritation Category 2A, Carcinogenicity Category 1A

Label elements

Hazard pictogram(s)





SIGNAL WORD

DANGER

Hazard statement(s)

` '	
H319	Causes serious eye irritation.
H350	May cause cancer.

Hazard(s) not otherwise specified

Not Applicable

Chemwatch: 9-536290 Page 2 of 9 Issue Date: 05/02/2018 Version No: 3.3 Print Date: 05/15/2018

Everlife Waterborne Paint Satin Sandstone - F10067

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P281	Use personal protective equipment as required.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statement(s) Storage

· · · · · · · · · · · · · · · · · · ·		
P405	Store locked up.	
Precautionary statement(s) Di	Secretary and A. S. Const.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.	
--	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1317-70-0	10-15	titanium dioxide (anatase)
1332-58-7	5.06	<u>kaolin</u>
57-55-6	1-5	propylene glycol
7664-41-7	<1	ammonia anhydrous liquefied

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to iron and its derivatives:

- Always treat symptoms rather than history.
- In general, however, toxic doses exceed 20 mg/kg of ingested material (as elemental iron) with lethal doses exceeding 180 mg/kg.
- Control of iron stores depend on variation in absorption rather than excretion. Absorption occurs through aspiration, ingestion and burned skin.
- Hepatic damage may progress to failure with hypoprothrombinaemia and hypoglycaemia. Hepatorenal syndrome may occur.
- Firon intoxication may also result in decreased cardiac output and increased cardiac pooling which subsequently produces hypotension.
- Forum iron should be analysed in symptomatic patients. Serum iron levels (2-4 hrs post-ingestion) greater that 100 ug/dL indicate poisoning with levels, in excess of 350 ug/dL, being potentially serious. Emesis or lavage (for obtunded patients with no gag reflex)are the usual means of decontamination.
- Activated charcoal does not effectively bind iron.
- Catharsis (using sodium sulfate or magnesium sulfate) may only be used if the patient already has diarrhoea.
- Deferoxamine is a specific chelator of ferric (3+) iron and is currently the antidote of choice. It should be administered parenterally. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

▶ There is no restriction on the type of extinguisher which may be used.

Chemwatch: 9-536290 Page 3 of 9 Issue Date: 05/02/2018 Version No: 3.3 Print Date: 05/15/2018

Everlife Waterborne Paint Satin Sandstone - F10067

Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear breathing apparatus plus protective gloves in the event of a fire.
- ▶ Non combustible. Fire/Explosion Hazard
 - ▶ Not considered a significant fire risk, however containers may burn.

May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe	hand	ling
------	------	------

- ► Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- ► DO NOT allow clothing wet with material to stay in contact with skin

Other information

Conditions for safe storage, including any incompatibilities

Suitable container

- ► Polyethylene or polypropylene container.
- ▶ Packing as recommended by manufacturer.

- ▶ reacts with strong acids, strong oxidisers Storage incompatibility
 - reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures - these reactions involves reduction of the oxide and are accompanied by incandescence
 - dust or powders can ignite and then explode in a carbon dioxide atmosphere
 - ▶ WARNING: Avoid or control reaction with peroxides. All transition metal peroxides should be considered as potentially explosive.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Titanium dioxide

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	titanium dioxide (anatase)	Rutile, Titanium oxide, Titanium peroxide	Not Available	Not Available	Not Available	Ca See Appendix A
US ACGIH Threshold Limit Values (TLV)	titanium dioxide (anatase)	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV® Basis: LRT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	titanium dioxide (anatase)	Titanium dioxide: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	kaolin	China clay, Clay, Hydrated aluminum silicate, Hydrite, Porcelain clay [Note: Main constituent of Kaolin is Kaolinite (Al2Si2O5(OH)4).]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	kaolin	Kaolin	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	kaolin	Kaolin: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	kaolin	Kaolin: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ammonia anhydrous liquefied	Anhydrous ammonia, Aqua ammonia, Aqueous ammonia [Note: Often used in an aqueous solution.]	18 mg/m3 / 25 ppm	27 mg/m3 / 35 ppm	Not Available	Not Available

Chemwatch: **9-536290** Page **4** of **9**

Version No: 3.3

Everlife Waterborne Paint Satin Sandstone - F10067

Issue Date: **05/02/2018**Print Date: **05/15/2018**

US ACGIH Threshold Limit Values (TLV)	ammonia anhydrous liquefied	Ammonia	25 ppm	35 ppm	Not Available	TLV® Basis: Eye dam; URT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ammonia anhydrous liquefied	Ammonia	35 mg/m3 / 50 ppm	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
titanium dioxide (anatase)	Titanium oxide; (Titanium dioxide)	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3	1,300 mg/m3	7,900 mg/m3
ammonia anhydrous liquefied	Ammonia	Not Available	Not Available	Not Available

Lucino Pour	October 1911	Poster HPLH
Ingredient	Original IDLH	Revised IDLH
titanium dioxide (anatase)	5000 mg/m3	Not Available
kaolin	Not Available	Not Available
propylene glycol	Not Available	Not Available
ammonia anhydrous liquefied	300 ppm	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Personal protection









- Safety glasses with side shields
- Chemical goggles

Eye and face protection Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- Hands/feet protection

▶ Wear safety footwear or safety gumboots, e.g. Rubber
The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.

Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Body protection

See Other protection below

- Other protection
- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges.
- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.
- Overalls.
- ▶ P.V.C.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

Chemwatch: 9-536290 Page 5 of 9

Version No: 3.3 **Everlife Waterborne Paint Satin Sandstone - F10067**

Issue Date: 05/02/2018 Print Date: 05/15/2018

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on t	toxicological effects
------------------	-----------------------

•			
Inhaled	The odour of isopropanol may give some warning of exposure, but odour fatigue may occur. Inhalation of isopropanol may produce irritation of the nose arthroat with sneezing, sore throat and runny nose.		
Ingestion	Swallowing 10 millilitres of isopropanol may cause serious injury; 100 millilitres may be fatal if not properly treated. The adult single lethal dose is approximately 250 millilitres.		
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. 511ipa		
Eye	This material can cause eye irritation and damage in some persons. Isopropanol vapour may cause mild eye irritation at 400 parts per million. Splashes may cause severe eye irritation, possible burns to the comea and eye damage.		
Chronic	There is sufficient evidence to suggest that this material directly causes cancer in humans. Chronic dust inhalation of kaolin, can cause kaolinosis from kaolin deposition in the lungs causing distinct lung markings, abnormal inflation of air sacs, and chronic lung diseases (nodular pneumoconiosis). This condition is made worse by long duration of occupational exposure and pre-existing chest infection. Pre-employment screening is recommended. Chronic excessive intake of iron have been associated with damage to the liver and pancreas. People with a genetic disposition to poor control over iron are at an increased risk. Long term, or repeated exposure of isopropanol may cause inco-ordination and tiredness. Repeated inhalation exposure to isopropanol may produce sleepiness, inco-ordination and liver degeneration.		
Everlife Waterborne Paint	TOXICITY	IRRITATION	

Everlife Waterborne Paint	TOXICITY	IRRITATION
Satin Sandstone - F10067	Not Available	Not Available
	TOXICITY	IRRITATION
titanium dioxide (anatase)	Inhalation (rat) LC50: >2.28 mg/l4 h ^[1]	Not Available
	Oral (rat) LD50: >2000 mg/kg ^[1]	
l Po	TOXICITY	IRRITATION
kaolin	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 11890 mg/kg ^[2]	Eye (rabbit): 100 mg - mild
propylene glycol	Oral (rat) LD50: 20000 mg/kg ^[2]	Eye (rabbit): 500 mg/24h - mild
		Skin(human):104 mg/3d Intermit Mod
		Skin(human):500 mg/7days mild
	TOXICITY	IRRITATION
ammonia anhydrous liquefied	Inhalation (rat) LC50: 1997.718 mg/l/4H ^[2]	Not Available
Legend:	Value obtained from Europe ECHA Registered Substances	- Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified

data extracted from RTECS - Register of Toxic Effect of chemical Substances

TITANIUM D	IOXIDE ((ANATASE)
------------	----------	-----------

Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system.

	ł		
A custo Tourisites	8	Canalina maniaita	
Acute Toxicity	0	Carcinogenicity	*
Skin Irritation/Corrosion	0	Reproductivity	0
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	0
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Version No: 3.3

Everlife Waterborne Paint Satin Sandstone - F10067

Issue Date: 05/02/2018 Print Date: 05/15/2018

Legena:

→ Data available out uoes not illi the chiena for classification
 ✓ - Data available to make classification

N - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Everlife Waterborne Paint Satin Sandstone - F10067	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	155mg/L	2
Charles Barries Arragan	EC50	48	Crustacea	>10mg/L	2
titanium dioxide (anatase)	EC50	72	Algae or other aquatic plants	5.83mg/L	4
	EC20	72	Algae or other aquatic plants	1.81mg/L	4
	NOEC	336	Fish	0.089mg/L	4
kaolin	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	710mg/L	4
propylene glycol	EC50	48	Crustacea	>1000mg/L	4
	EC50	96	Algae or other aquatic plants	19000mg/L	2
	NOEC	168	Fish	98mg/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURC
	LC50	96	Fish	0.068mg/L	2
mmonia anhydrous liquefied	EC50	48	Crustacea	0.179mg/L	5
	NOEC	Not Available	Fish	0.0015mg/L	5

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Bentonite and kaolin have low toxicity to aquatic species, a large number of which have been tested

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide (anatase)	HIGH	HIGH
propylene glycol	LOW	LOW
ammonia anhydrous liquefied	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide (anatase)	LOW (BCF = 10)
propylene glycol	LOW (BCF = 1)
ammonia anhydrous liquefied	LOW (LogKOW = 0.229)

Mobility in soil

Ingredient	Mobility
titanium dioxide (anatase)	LOW (KOC = 23.74)
propylene glycol	HIGH (KOC = 1)
ammonia anhydrous liquefied	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ► Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.
 - ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
 - ▶ It may be necessary to collect all wash water for treatment before disposal.

Version No: 3.3

- ► Recycle wherever possible.
- ► Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

TITANIUM DIOXIDE (ANATASE)(1317-70-0) IS FOUND ON THE FOLLOWING REGULAT	TORY LISTS
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
Monographs	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - Alaska Limits for Air Contaminants	Contaminants
US - California Proposition 65 - Carcinogens	US - Washington Permissible exposure limits of air contaminants
US - Hawaii Air Contaminant Limits	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Idaho - Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV)
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Michigan Exposure Limits for Air Contaminants	US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive)
US - Minnesota Permissible Exposure Limits (PELs)	Rule
US - Oregon Permissible Exposure Limits (Z-1)	US NIOSH Recommended Exposure Limits (RELs)
US - Pennsylvania - Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Rhode Island Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
	US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification Requirements

KAOLIN(1332-58-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV)
US - Oregon Permissible Exposure Limits (Z-1)	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Pennsylvania - Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Rhode Island Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances

US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

PROPYLENE GLYCOL(57-55-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS	
US - Pennsylvania - Hazardous Substance List	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Rhode Island Hazardous Substance List	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US AIHA Workplace Environmental Exposure Levels (WEELs)	US TSCA Chemical Substance Inventory - Interim List of Active Substances

AMMONIA ANHYDROUS LIQUEFIED(7664-41-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

7	
International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)	US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
(CRELs)	US ACGIH Threshold Limit Values (TLV)
US - California Permissible Exposure Limits for Chemical Contaminants	US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)
US - Hawaii Air Contaminant Limits	US CWA (Clean Water Act) - List of Hazardous Substances
US - Idaho - Limits for Air Contaminants	US EPCRA Section 313 Chemical List
US - Massachusetts - Right To Know Listed Chemicals	US NIOSH Recommended Exposure Limits (RELs)
US - Michigan Exposure Limits for Air Contaminants	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Minnesota Permissible Exposure Limits (PELs)	US SARA Section 302 Extremely Hazardous Substances
US - Oregon Permissible Exposure Limits (Z-1)	US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants
US - Pennsylvania - Hazardous Substance List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Rhode Island Hazardous Substance List	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	

Version No: 3.3

Everlife Waterborne Paint Satin Sandstone - F10067

Issue Date: **05/02/2018**Print Date: **05/15/2018**

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
Ammonia	100	45.4

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Titanium dioxide (airborne, unbound particles of respirable size) Listed

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	N (kaolin; propylene glycol; ammonia anhydrous liquefied)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (kaolin)
Korea - KECI	Υ
New Zealand - NZIoC	Y
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	05/02/2018
Initial Date	05/03/2018

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

Ingredients with multiple cas numbers

Name	CAS No
titanium dioxide (anatase)	1317-70-0, 13463-67-7

Chemwatch: 9-536290 Page 9 of 9 Issue Date: 05/02/2018 Version No: 3.3 Print Date: 05/15/2018

Everlife Waterborne Paint Satin Sandstone - F10067

kaolin

1332-58-7, 71888-52-3, 1026990-70-4, 12198-85-5, 12199-11-0, 190086-05-6, 290817-34-4, 384842-32-4, 39406-22-9, 52624-41-6, 849104-81-0, 903527-69-5, 90803-81-9, 944250-63-9, 95077-05-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.