



Fix Rust Alkyd Primer Red Oxide - F50071

ICP Building Solutions Group (Canada)

Version No: 4.5

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 01/12/2022

Print Date: 01/12/2022

S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Fix Rust Alkyd Primer Red Oxide - F50071
Synonyms	Not Available
Proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Rust preventive primer
--------------------------	------------------------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group (Canada)
Address	150 Dascomb Road MA 01810 United States
Telephone	978-623-9980
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Flammable Liquids Category 3, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Repeated Exposure Category 2, Carcinogenicity Category 1A, Reproductive Toxicity Category 2, Sensitisation (Skin) Category 1, Aspiration Hazard Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
----------------	--

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H226	Flammable liquid and vapour.
------	------------------------------

Fix Rust Alkyd Primer Red Oxide - F50071

H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H350	May cause cancer.
H361	Suspected of damaging fertility or the unborn child.
H317	May cause an allergic skin reaction.
H304	May be fatal if swallowed and enters airways.
H412	Harmful to aquatic life with long lasting effects.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statement(s) Prevention

P202	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof (electrical/ventilating/lighting) equipment
P242	Use only non-sparking tools
P243	Take precautions against static discharge
P261	Avoid breathing dust/fumes/gas/mist/vapors/spray
P264	Wash thoroughly after handling
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P331	Do NOT induce vomiting.
P312	Call a POISON CENTER/doctor if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333+P313	IF Skin irritation or rash occurs: Get medical advice/attention.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse SKIN with water (or shower)
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P337+P313	IF Eye irritation persists: Get medical advice/attention.
P308+P313	IF Exposed or concerned: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
14808-60-7	.1-1	<u>silica crystalline - quartz</u>
100-41-4	.1-1	<u>ethylbenzene</u>
64741-91-9.	1-5	<u>C14-20 aliphatics (<=2% aromatics)</u>
96-29-7	.1-1	<u>methyl ethyl ketoxime</u>
64742-95-6.	1-5	<u>aromatic 150</u>
64742-47-8	5-10	<u>distillates_petroleum_light_hydrated</u>
22464-99-9	.1-1	<u>zirconium 2-ethylhexanoate</u>

Continued...

Fix Rust Alkyd Primer Red Oxide - F50071

CAS No	%[weight]	Name
1333-86-4	.1-1	carbon black
14464-46-1	1-5	cristobalite

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Liquid and vapour are flammable. ▶ Moderate fire hazard when exposed to heat or flame. <p>Combustion products include: carbon dioxide (CO₂) carbon monoxide (CO) metal oxides other pyrolysis products typical of burning organic material.</p>

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately.
Major Spills	<ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard.

Fix Rust Alkyd Primer Red Oxide - F50071

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. ▶ Electrostatic discharge may be generated during pumping - this may result in fire. ▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment. ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of overexposure occurs. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	<ul style="list-style-type: none"> ▶ Store in original containers in approved flammable liquid storage area. ▶ Store away from incompatible materials in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Packing as supplied by manufacturer. ▶ Plastic containers may only be used if approved for flammable liquid. ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
Storage incompatibility	<ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO ₂ +2) mg/m ³ / 250 (%SiO ₂ +5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m ³	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	silica crystalline - quartz	Silica, crystalline - α-quartz and cristobalite (Respirable particulate matter)	0.025 mg/m ³	Not Available	Not Available	A2
US OSHA Permissible Exposure Limits (PELs) Table Z-1	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m ³	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ethylbenzene	Ethyl benzene	100 ppm / 435 mg/m ³	545 mg/m ³ / 125 ppm	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethylbenzene	Ethyl benzene	20 ppm	Not Available	Not Available	(); A3; BEI
US OSHA Permissible Exposure Limits (PELs) Table Z-1	C14-20 aliphatics (<=2% aromatics)	Oil mist, mineral	5 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	C14-20 aliphatics (<=2% aromatics)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m ³	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-1	distillates, petroleum, light, hydrotreated	Oil mist, mineral	5 mg/m ³	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	distillates, petroleum, light, hydrotreated	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m ³	Not Available	Not Available	A4
US ACGIH Threshold Limit Values (TLV)	distillates, petroleum, light, hydrotreated	Mineral oil, excluding metal working fluids - Poorly and mildly refined	Not Available	Not Available	Not Available	A2
US OSHA Permissible Exposure Limits (PELs) Table Z-3	zirconium 2-ethylhexanoate	Inert or Nuisance Dust: Total Dust	15 mg/m ³ / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	zirconium 2-ethylhexanoate	Inert or Nuisance Dust: Respirable fraction	5 mg/m ³ / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	zirconium 2-ethylhexanoate	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m ³	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	zirconium 2-ethylhexanoate	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m ³	Not Available	Not Available	Not Available

Fix Rust Alkyd Primer Red Oxide - F50071

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	zirconium 2-ethylhexanoate	Zirconium compounds (as Zr)	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	zirconium 2-ethylhexanoate	Zirconium compounds (as Zr)	5 mg/m3	10 mg/m3	Not Available	[*Note: The REL applies to all zirconium compounds (as Zr) except Zirconium tetrachloride.]
US NIOSH Recommended Exposure Limits (RELs)	zirconium 2-ethylhexanoate	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D
US ACGIH Threshold Limit Values (TLV)	zirconium 2-ethylhexanoate	Zirconium and compounds, as Zr	5 mg/m3	10 mg/m3	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See Appendix C
US ACGIH Threshold Limit Values (TLV)	carbon black	Carbon black (Inhalable particulate matter)	3 mg/m3	Not Available	Not Available	A3
US OSHA Permissible Exposure Limits (PELs) Table Z-3	crystalite	Silica: Crystalline: Cristobalite	Not Available	Not Available	Not Available	Use ½ the value calculated from the count or mass formulae for quartz.
US OSHA Permissible Exposure Limits (PELs) Table Z-1	crystalite	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	crystalite	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	crystalite	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D
US ACGIH Threshold Limit Values (TLV)	crystalite	Silica, crystalline - α-quartz and cristobalite (Respirable particulate matter)	0.025 mg/m3	Not Available	Not Available	A2

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
silica crystalline - quartz	0.075 mg/m3	33 mg/m3	200 mg/m3
ethylbenzene	Not Available	Not Available	Not Available
C14-20 aliphatics (<=2% aromatics)	1,100 mg/m3	1,800 mg/m3	40,000 mg/m3
methyl ethyl ketoxime	30 ppm	56 ppm	250 ppm
aromatic 150	1,200 mg/m3	6,700 mg/m3	40,000 mg/m3
distillates, petroleum, light, hydrotreated	140 mg/m3	1,500 mg/m3	8,900 mg/m3
carbon black	9 mg/m3	99 mg/m3	590 mg/m3
cristobalite	0.075 mg/m3	33 mg/m3	200 mg/m3

Ingredient	Original IDLH	Revised IDLH
silica crystalline - quartz	25 mg/m3 / 50 mg/m3	Not Available
ethylbenzene	800 ppm	Not Available
C14-20 aliphatics (<=2% aromatics)	2,500 mg/m3	Not Available
methyl ethyl ketoxime	Not Available	Not Available
aromatic 150	Not Available	Not Available
distillates, petroleum, light, hydrotreated	2,500 mg/m3	Not Available
zirconium 2-ethylhexanoate	25 mg/m3	Not Available
carbon black	1,750 mg/m3	Not Available
cristobalite	Not Available	Not Available


Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
methyl ethyl ketoxime	D	> 0.1 to ≤ 1 ppm
aromatic 150	E	≤ 0.1 ppm

Notes: Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

Fix Rust Alkyd Primer Red Oxide - F50071

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ PVC Apron. ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

If inhalation risk above the TLV exists, wear approved dust respirator.

Use respirators with protection factors appropriate for the exposure level.

- ▶ Up to 5 X TLV, use valveless mask type; up to 10 X TLV, use 1/2 mask dust respirator
- ▶ Up to 50 X TLV, use full face dust respirator or demand type C air supplied respirator
- ▶ Up to 500 X TLV, use powered air-purifying dust respirator or a Type C pressure demand supplied-air respirator
- ▶ Over 500 X TLV wear full-face self-contained breathing apparatus with positive pressure mode or a combination respirator with a Type C positive pressure supplied-air full-face respirator and an auxiliary self-contained breathing apparatus operated in pressure demand or other positive pressure mode
- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	40.5	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (%)	Not Available

Continued...

Fix Rust Alkyd Primer Red Oxide - F50071

Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
--------------------------	---------------	---------	---------------

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material. Crystalline silicas activate the inflammatory response of white blood cells after they injure the lung epithelium. Chronic exposure to crystalline silicas reduces lung capacity and predisposes to chest infections. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Fix Rust Alkyd Primer Red Oxide - F50071	TOXICITY	IRRITATION
	Not Available	Not Available
silica crystalline - quartz	TOXICITY	IRRITATION
	Oral (Rat) LD50; 500 mg/kg ^[2]	Not Available
ethylbenzene	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 17800 mg/kg ^[2]	Eye (rabbit): 500 mg - SEVERE
	Inhalation(Rat) LC50; 17.2 mg/4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; 3500 mg/kg ^[2]	Skin (rabbit): 15 mg/24h mild Skin: no adverse effect observed (not irritating) ^[1]
C14-20 aliphatics (<=2% aromatics)	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye : Not irritating (OECD 405) *
	Inhalation(Rat) LC50; 4.6 mg/4h ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; 7400 mg/kg ^[2]	Skin : Not irritating (OECD 404)* Skin: adverse effect observed (irritating) ^[1]
methyl ethyl ketoxime	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >184<1840 mg/kg ^[1]	Eye (rabbit): 0.1 ml - SEVERE
	Inhalation(Rat) LC50; >4.83 mg/4h ^[1]	
	Oral (Rat) LD50; >900 mg/kg ^[1]	

Fix Rust Alkyd Primer Red Oxide - F50071

	TOXICITY	IRRITATION
aromatic 150	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation(Rat) LC50; >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50; >4500 mg/kg ^[1]	
distillates, petroleum, light, hydrotreated	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Inhalation(Rat) LC50; >4.3 mg/l4h ^[1]	Skin: adverse effect observed (irritating) ^[1]
	Oral (Rat) LD50; >5000 mg/kg ^[2]	
zirconium 2-ethylhexanoate	dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available
	Inhalation(Rat) LC50; >4.3 mg/l4h ^[1]	
	Oral (Rat) LD50; 2043 mg/kg ^[1]	
carbon black	Dermal (rabbit) LD50: >3000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (Rat) LD50; >8000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
cristobalite	Not Available	Not Available
	Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

Fix Rust Alkyd Primer Red Oxide - F50071	Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.
ETHYLBENZENE	Liver changes, uterual tract, effects on fertility, foetotoxicity, specific developmental abnormalities (musculoskeletal system) recorded. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Ethylbenzene is readily absorbed when inhaled, swallowed or in contact with the skin. It is distributed throughout the body, and passed out through urine. NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals producing damage or change to cellular DNA.
C14-20 ALIPHATICS (<=2% AROMATICS)	*Exxsol D 100 SDS
METHYL ETHYL KETOXIME	Mammalian lymphocyte mutagen *Huls Canada ** Merck For methyl ethyl ketoxime (MEKO): At medium to high concentrations, MEKO increased the rate of liver tumours in animal testing. This seems to be due to the breakdown of MEKO into a cancer-causing substance, and occurred more often in males.
AROMATIC 150	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system. This product contains toluene, and animal studies suggest high concentrations of toluene lead to hearing loss.
DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED	Kerosene may produce varying ranges of skin irritation, and a reversible eye irritation (if eyes are washed). Skin may be cracked or flaky and/or leathery, with crusts and/or hair loss.
ZIRCONIUM 2-ETHYLHEXANOATE	For aliphatic fatty acids (and salts) Acute oral (gavage) toxicity: The acute oral LD50 values in rats for both were greater than >2000 mg/kg bw Clinical signs were generally associated with poor condition following administration of high doses (salivation, diarrhoea, staining, piloerection and lethargy). There were no adverse effects on body weight in any study In some studies, excess test substance and/or irritation in the gastrointestinal tract was observed at necropsy. Skin and eye irritation potential, with a few stated exceptions, is chain length dependent and decreases with increasing chain length According to several OECD test regimes the animal skin irritation studies indicate that the C6-10 aliphatic acids are severely irritating or corrosive, while the C12 aliphatic acid is irritating, and the C14-22 aliphatic acids generally are not irritating or mildly irritating. Human skin irritation studies using more realistic exposures (30-minute, 1-hour or 24-hours) indicate that the aliphatic acids have sufficient, good or very good skin compatibility. Animal eye irritation studies indicate that among the aliphatic acids, the C8-12 aliphatic acids are irritating to the eye while the C14-22 aliphatic acids are not irritating. Fatty acid salts of low acute toxicity. Their potential to irritate the skin and eyes is dependent on chain length.
CARBON BLACK	Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported
CRISTOBALITE	Inhalation (human) TCLo: 16 mppcf*/8H/17.9y-I * Millions of particles per cubic foot
Fix Rust Alkyd Primer Red Oxide - F50071 & METHYL ETHYL KETOXIME	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.
SILICA CRYSTALLINE - QUARTZ & CRISTOBALITE	WARNING: For inhalation exposure <u>ONLY</u> : This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans . This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite.

Fix Rust Alkyd Primer Red Oxide - F50071

ETHYLBENZENE & CARBON BLACK	WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
C14-20 ALIPHATICS (<=2% AROMATICS) & DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED	Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins. The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species.
DISTILLATES, PETROLEUM, LIGHT, HYDROTREATED & ZIRCONIUM 2-ETHYLHEXANOATE & CARBON BLACK	No significant acute toxicological data identified in literature search.

Acute Toxicity	✗	Carcinogenicity	✓
Skin Irritation/Corrosion	✗	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✓

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Fix Rust Alkyd Primer Red Oxide - F50071	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
silica crystalline - quartz	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
ethylbenzene	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	720h	Fish	0.381mg/L	4
	LC50	96h	Fish	3.381-4.075mg/L	4
	EC50	72h	Algae or other aquatic plants	4.6mg/l	1
	EC50	48h	Crustacea	1.37-4.4mg/l	4
	EC50	96h	Algae or other aquatic plants	3.6mg/l	2
C14-20 aliphatics (<=2% aromatics)	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	<0.03mg/l	1
	NOEC(ECx)	3072h	Fish	1mg/l	1
methyl ethyl ketoxime	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	0.5-0.6	7
	NOEC(ECx)	72h	Algae or other aquatic plants	~1.02mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	72h	Algae or other aquatic plants	~6.09mg/l	2
	EC50	48h	Crustacea	~201mg/l	2
aromatic 150	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	0.95mg/l	1
	LC50	96h	Fish	0.58mg/l	2
	EC50	72h	Algae or other aquatic plants	<1mg/l	1
	EC50	48h	Crustacea	0.95mg/l	1
	EC50	96h	Algae or other aquatic plants	1mg/l	2
	NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	1
	EC50	72h	Algae or other aquatic plants	19mg/l	1
	EC50	48h	Crustacea	6.14mg/l	1
	EC50	96h	Algae or other aquatic plants	64mg/l	2
distillates, petroleum, light, hydrotreated	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	3072h	Fish	1mg/l	1
zirconium 2-ethylhexanoate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	>100mg/l	2

Continued...

Fix Rust Alkyd Primer Red Oxide - F50071

	EC50	72h	Algae or other aquatic plants	49.3mg/l	2
	EC50	48h	Crustacea	>0.17mg/l	2
	EC50(ECx)	48h	Crustacea	>0.17mg/l	2
carbon black	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	24h	Crustacea	3200mg/l	1
	LC50	96h	Fish	>100mg/l	2
	EC50	72h	Algae or other aquatic plants	>0.2mg/l	2
	EC50	48h	Crustacea	33.076-41.968mg/l	4
cristobalite	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

When spilled this product may act as a typical oil, causing a film, sheen, emulsion or sludge at or beneath the surface of the body of water. The oil film on water surface may physically affect the aquatic organisms, due to the interruption of the oxygen transfer between the air and the water

Oils of any kind can cause:

- ▶ drowning of water-fowl due to lack of buoyancy, loss of insulating capacity of feathers, starvation and vulnerability to predators due to lack of mobility
- ▶ lethal effects on fish by coating gill surfaces, preventing respiration
- ▶ asphyxiation of benthic life forms when floating masses become engaged with surface debris and settle on the bottom and
- ▶ adverse aesthetic effects of fouled shoreline and beaches

In case of accidental releases on the soil, a fine film is formed on the soil, which prevents the plant respiration process and the soil particle saturation.

Drinking Water Standards: hydrocarbon total: 10 ug/l (UK max.).

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylbenzene	HIGH (Half-life = 228 days)	LOW (Half-life = 3.57 days)
methyl ethyl ketoxime	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylbenzene	LOW (BCF = 79.43)
C14-20 aliphatics (<=2% aromatics)	LOW (BCF = 159)
methyl ethyl ketoxime	LOW (BCF = 5.8)
aromatic 150	LOW (BCF = 159)
distillates, petroleum, light, hydrotreated	LOW (BCF = 159)

Mobility in soil

Ingredient	Mobility
ethylbenzene	LOW (KOC = 517.8)
methyl ethyl ketoxime	LOW (KOC = 130.8)

SECTION 13 Disposal considerations


Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ Recycle wherever possible. ▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
-------------------------------------	---

SECTION 14 Transport information

Labels Required

Fix Rust Alkyd Primer Red Oxide - F50071

	
Marine Pollutant	NO

Land transport (DOT)

UN number	1263	
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound	
Transport hazard class(es)	Class	3
	Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Hazard Label	3
	Special provisions	367, B1, B52, B131, IB3, T2, TP1, TP29

Air transport (ICAO-IATA / DGR)

UN number	1263	
UN proper shipping name	Paint related material (including paint thinning or reducing compounds)	
Transport hazard class(es)	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	A3 A72 A192
	Cargo Only Packing Instructions	366
	Cargo Only Maximum Qty / Pack	220 L
	Passenger and Cargo Packing Instructions	355
	Passenger and Cargo Maximum Qty / Pack	60 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y344
Passenger and Cargo Limited Maximum Qty / Pack	10 L	

Sea transport (IMDG-Code / GGVSee)

UN number	1263	
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
Transport hazard class(es)	IMDG Class	3
	IMDG Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number	F-E , S-E
	Special provisions	163 223 367 955
	Limited Quantities	5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
silica crystalline - quartz	Not Available
ethylbenzene	Not Available
C14-20 aliphatics (<=2% aromatics)	Not Available
methyl ethyl ketoxime	Not Available
aromatic 150	Not Available
distillates, petroleum, light, hydrotreated	Not Available

Continued...

Fix Rust Alkyd Primer Red Oxide - F50071

Product name	Group
zirconium 2-ethylhexanoate	Not Available
carbon black	Not Available
crystalite	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
silica crystalline - quartz	Not Available
ethylbenzene	Not Available
C14-20 aliphatics (<=2% aromatics)	Not Available
methyl ethyl ketoxime	Not Available
aromatic 150	Not Available
distillates, petroleum, light, hydrotreated	Not Available
zirconium 2-ethylhexanoate	Not Available
carbon black	Not Available
crystalite	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

ethylbenzene is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Carcinogens

US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US CWA (Clean Water Act) - List of Hazardous Substances

US CWA (Clean Water Act) - Priority Pollutants

US CWA (Clean Water Act) - Toxic Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

C14-20 aliphatics (<=2% aromatics) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

methyl ethyl ketoxime is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US TSCA Section 4/12 (b) - Sunset Dates/Status

aromatic 150 is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

distillates, petroleum, light, hydrotreated is found on the following regulatory lists

Fix Rust Alkyd Primer Red Oxide - F50071

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US ACGIH Threshold Limit Values (TLV)

zirconium 2-ethylhexanoate is found on the following regulatory lists

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

carbon black is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

crystalite is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312 hazard categories**

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	Yes
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	Yes
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylbenzene	1000	454

Continued...

Fix Rust Alkyd Primer Red Oxide - F50071

State Regulations

US. California Proposition 65

WARNING: This product can expose you to chemicals including **silica crystalline - quartz, ethylbenzene, distillates, petroleum, light, hydrotreated, carbon black, cristobalite**, which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (silica crystalline - quartz; ethylbenzene; C14-20 aliphatics (<=2% aromatics); methyl ethyl ketoxime; aromatic 150; distillates, petroleum, light, hydrotreated; zirconium 2-ethylhexanoate; carbon black; cristobalite) aromatics;="" methyl="" ethyl="" ketoxime;="" aromatic="" 150;="" distillates,="" petroleum,="" light,="" hydrotreated;="" zirconium="" 2-ethylhexanoate;="" carbon="" black;="">
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (aromatic 150)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (zirconium 2-ethylhexanoate)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	01/12/2022
Initial Date	03/14/2020

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
3.5	01/12/2022	Advice to Doctor, Chronic Health, Classification, Exposure Standard, Fire Fighter (fire/explosion hazard), Fire Fighter (fire fighting), Ingredients, Storage (storage incompatibility)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index
 AIIC: Australian Inventory of Industrial Chemicals
 DSL: Domestic Substances List
 NDSL: Non-Domestic Substances List
 IECSC: Inventory of Existing Chemical Substance in China
 EINECS: European INventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
 NLP: No-Longer Polymers
 ENCS: Existing and New Chemical Substances Inventory
 KECI: Korea Existing Chemicals Inventory

Fix Rust Alkyd Primer Red Oxide - F50071

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.