

ICP Construction

Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Everlife Waterborne Enamel High Gloss Medium Gray - F52113
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Paint

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction
Address	150 Dascomb Road Andover MA United States
Telephone	978-623-9980
Fax	Not Available
Website	http://www.icp-construction.com/
Email	Not Available

Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Eye Irritation Category 2A, Carcinogenicity Category 1A

Label elements

Hazard pictogram(s)	
SIGNAL WORD	DANGER

Hazard statement(s)

H319	Causes serious eye irritation.
H350	May cause cancer.

Hazard(s) not otherwise specified

Not Applicable

Issue Date: 09/12/2018

Print Date: 09/12/2018 S.GHS.USA.EN

Precautionary statement(s) General		
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
Precautionary statement(s) Pr	revention	
P201	Obtain special instructions before use.	
P281	Use personal protective equipment as required.	
Precautionary statement(s) Ro P308+P313	esponse IF exposed or concerned: Get medical advice/attention.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
Precautionary statement(s) Storage		
P405	Store locked up.	
Precautionary statement(s) Disposal		
P501	Dispose of contents/container in accordance with local regulations.	

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1332-58-7	10.14	kaolin
1317-70-0	1-10	titanium dioxide (anatase)
57-55-6	1-5	propylene glycol
1333-86-4	<1	carbon black

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description	of first	t aid measur	es
-------------	----------	--------------	----

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. DO NOT allow clothing wet with material to stay in contact with skin
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer.
Storage incompatibility	 Titanium dioxide reacts with strong acids, strong oxidisers reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures - these reactions involves reduction of the oxide and are accompanied by incandescence dust or powders can ignite and then explode in a carbon dioxide atmosphere None known

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	kaolin	China clay, Clay, Hydrated aluminum silicate, Hydrite, Porcelain clay [Note: Main constituent of Kaolin is Kaolinite (Al2Si2O5(OH)4).]	10 (total), 5 (resp) mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	kaolin	Kaolin	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	kaolin	Kaolin: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	kaolin	Kaolin: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	titanium dioxide (anatase)	Rutile, Titanium oxide, Titanium peroxide	Not Available	Not Available	Not Available	Ca See Appendix A
US ACGIH Threshold Limit Values (TLV)	titanium dioxide (anatase)	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV® Basis: LRT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	titanium dioxide (anatase)	Titanium dioxide: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Acetylene black, Channel black, Furnace black, Lamp black, Thermal black	3.5 mg/m3	Not Available	Not Available	Ca See Appendix A See Appendix C
US ACGIH Threshold Limit Values (TLV)	carbon black	Carbon black	3 mg/m3	Not Available	Not Available	TLV® Basis: Bronchitis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3

Version No: 1.1

Everlife Waterborne Enamel High Gloss Medium Gray - F52113

titanium dioxide (anatase)	Titanium oxide; (Titanium dioxide)	30 m	g/m3	330 mg/m3	2,000 mg/m3
propylene glycol	Polypropylene glycols	30 m	g/m3	330 mg/m3	2,000 mg/m3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 m	g/m3	1,300 mg/m3	7,900 mg/m3
carbon black	Carbon black	9 mg	/m3	99 mg/m3	590 mg/m3
Ingredient	Original IDLH		Revised IDLH	1	
kaolin	Not Available		Not Available		
titanium dioxide (anatase)	5,000 mg/m3	5,000 mg/m3		Not Available	
propylene glycol	Not Available	Not Available		Not Available	
carbon black	1,750 mg/m3	1,750 mg/m3		Not Available	

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Body protection	See Other protection below
Other protection	 Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. P.V.C.

Respiratory protection

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity See section 7

Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The odour of isopropanol may give some warning of exposure, but odour fatigue may occur. Inhalation of isopropanol may produce irritation of the nose and throat with sneezing, sore throat and runny nose.				
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Swallowing 10 millilitres of isopropanol may cause serious injury; 100 millilitres may be fatal if not properly treated. The adult single lethal dose is approximately 250 millilitres.				
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. 511ipa				
Eye	This material can cause eye irritation and damage in some persons. Isopropanol vapour may cause mild eye irritation at 400 parts per million. Splashes may cause severe eye irritation, possible burns to the cornea and eye damage.				
Chronic	There is sufficient evidence to suggest that this material direc Chronic dust inhalation of kaolin, can cause kaolinosis from k and chronic lung diseases (nodular pneumoconiosis). This cor infection. Pre-employment screening is recommended. Long term, or repeated exposure of isopropanol may cause in Repeated inhalation exposure to isopropanol may produce sle	aolin deposition in the lungs causing distinct lundition is made worse by long duration of occu co-ordination and tiredness.	pational exposure and pre-existing chest		
Everlife Waterborne Enamel		IDDITATION			
High Gloss Medium Gray -	TOXICITY Not Available	IRRITATION Not Available			
F52113		Not Available			
	ΤΟΧΙΟΙΤΥ	IRRITATION			
kaolin	Not Available	Not Available			
		Not Available			
	ΤΟΧΙΟΙΤΥ		IRRITATION		
titanium dioxide (anatase)			Not Available		
titanium dioxide (anatase)	Inhalation (rat) LC50: >2.28 mg/l4 h ^[1]				
	Oral (rat) LD50: >2000 mg/kg ^[1]				
	ΤΟΧΙCITY	IRRITATION			
	Dermal (rabbit) LD50: 11890 mg/kg ^[2]	Eye (rabbit): 100 mg - mild			
propylene glycol	Oral (rat) LD50: 20000 mg/kg ^[2]	Eye (rabbit): 500 mg/24h - r	nild		
		Skin(human):104 mg/3d Inte			
		Skin(human):500 mg/7days	mild		
	l				
	ΤΟΧΙΟΙΤΥ		IRRITATION		
carbon black	Dermal (rabbit) LD50: >3000 mg/kg ^[2]		Not Available		
	Oral (rat) LD50: >10000 mg/kg ^[1]				
Legend:	1. Value obtained from Europe ECHA Registered Substances data extracted from RTECS - Register of Toxic Effect of cherr		facturer's SDS. Unless otherwise specified		
KAOLIN	For bentonite clays: Bentonite (CAS No. 1302-78-9) consists of a group of clave to	rmed by crystallization of vitreous volcanic ash	as that ware deposited in water. The expect		

KAOLIN	Bentonite (CAS No. 1302-78-9) consists of a group of clays formed by crystallization of vitreous volcanic ashes that were deposited in water. The expected acute oral toxicity of bentonite in humans is very low.
TITANIUM DIOXIDE (ANATASE)	Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system.

Everlife Waterborne Enamel High G	Bloss Medium Gray - F52113
-----------------------------------	----------------------------

PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low; large amounts are needed to cause perceptible health damage in humans. Serious toxicity generally occurs only at blood concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time; this is nearly impossible with consuming foods or supplements which contain 1g/kg of PG at most. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.				
CARBON BLACK	WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported				
KAOLIN & CARBON BLACK	No significant acute toxicological data identified in literati	No significant acute toxicological data identified in literature search.			
Acute Toxicity	0	Carcinogenicity	v		
-			-		
Skin Irritation/Corrosion	0	Reproductivity	0		
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	\otimes		
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0		
Mutagenicity	\otimes	Aspiration Hazard	\otimes		
		✓ - D	hata available but does not fill the criteria for classification hata available to make classification Data Not Available to make classification		

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Everlife Waterborne Enamel High Gloss Medium Gray -	ENDPOINT	TEST DURATION (HR)			SPECIES	VALUE		SOURCE
F52113	Not Available	No	ot Available		Not Available	Not Availal	ble	Not Available
	ENDPOINT	TE	ST DURATION (HR)		SPECIES	VALUE		SOURCE
kaolin	Not Available	Not Available			Not Available	Not Available		Not Available
	ENDROINT	TEAT		00500	50			SOURCE
	ENDPOINT	TEST DURATION (HR)			SPECIES		VALUE	
	LC50	96		Fish			155mg/L	2
titanium dioxide (anatase)	EC50	48			Crustacea		>10mg/L	2
	EC50	72			Algae or other aquatic plants		5.83mg/L	4
	EC20	72			Algae or other aquatic plants		1.81mg/L	4
	NOEC	OEC 336 Fish				0.089mg/L	4	
	ENDPOINT	TEST DURATION (HR)		SPECIE	SPECIES		VALUE	SOURCE
	LC50	96		Fish	Fish		710mg/L	4
propylene glycol	EC50	48		Crustac	Crustacea		>1000mg/L	4
	EC50	96		Algae o	r other aquatic plants		19000mg/L	2
	NOEC	168		Fish			98mg/L	4
	ENDPOINT	т	EST DURATION (HR)		SPECIES	VALUE		SOURCE
carbon black	LC50	96			Fish	=1000n	ng/L	1
	NOEC	9	6		Fish	=1000n	ng/L	1
Legend:			city Data 2. Europe ECHA F a (Estimated) 4. US EPA, E					

Bentonite and kaolin have low toxicity to aquatic species, a large number of which have been tested

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide (anatase)	HIGH	HIGH
propylene glycol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide (anatase)	LOW (BCF = 10)
propylene glycol	LOW (BCF = 1)

Mobility in soil

Ingredient	Mobility
titanium dioxide (anatase)	LOW (KOC = 23.74)
propylene glycol	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods Product / Packaging disposal Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

SECTION 14 TRANSPORT INFORMATION

L	abels Required	
	Marine Pollutant	NO
L	and transport (DOT): NOT R	EGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

KAOLIN(1332-58-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Permissible Exposure Limits for Chemical Contaminants	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Minnesota Permissible Exposure Limits (PELs)	US ACGIH Threshold Limit Values (TLV)
US - Oregon Permissible Exposure Limits (Z-1)	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Pennsylvania - Hazardous Substance List	US NIOSH Recommended Exposure Limits (RELs)
US - Rhode Island Hazardous Substance List	US OSHA Permissible Exposure Levels (PELs) - Table Z1
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants	US TSCA Chemical Substance Inventory - Interim List of Active Substances
TITANIUM DIOXIDE (ANATASE)(1317-70-0) IS FOUND ON THE FOLLOWING REGULATOR	Y LISTS
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
Monographs	Contaminants
US - Alaska Limits for Air Contaminants	US - Washington Permissible exposure limits of air contaminants
US - California Proposition 65 - Carcinogens	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants

Rule

Requirements

US - Hawaii Air Contaminant I	imits

- US Idaho Limits for Air Contaminants
- US Massachusetts Right To Know Listed Chemicals
- US Michigan Exposure Limits for Air Contaminants
- US Minnesota Permissible Exposure Limits (PELs)
- US Oregon Permissible Exposure Limits (7-1)
- US Pennsylvania Hazardous Substance List
- US Rhode Island Hazardous Substance List
- US Tennessee Occupational Exposure Limits Limits For Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants

PROPYLENE GLYCOL(57-55-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - Pennsylvania - Hazardous Substance List

- US Rhode Island Hazardous Substance List
- US Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values
- US AIHA Workplace Environmental Exposure Levels (WEELs)

CARBON BLACK(1333-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US TSCA Section 5(a)(2) - Significant New Use Rules (SNURs)

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US NIOSH Recommended Exposure Limits (RELs)

US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants

US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Version No: 1.1

Everlife Waterborne Enamel High Gloss Medium Gray - F52113

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs	US - Rhode Island Hazardous Substance List
	US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants
US - Alaska Limits for Air Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
US - California Permissible Exposure Limits for Chemical Contaminants	US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air
US - California Proposition 65 - Carcinogens	Contaminants
US - Hawaii Air Contaminant Limits	US - Washington Permissible exposure limits of air contaminants
US - Idaho - Limits for Air Contaminants	US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
US - Massachusetts - Right To Know Listed Chemicals	US ACGIH Threshold Limit Values (TLV)
US - Michigan Exposure Limits for Air Contaminants	US ACGIH Threshold Limit Values (TLV) - Carcinogens
US - Minnesota Permissible Exposure Limits (PELs)	US NIOSH Recommended Exposure Limits (RELs)
US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL):	US OSHA Permissible Exposure Levels (PELs) - Table Z1
Carcinogens	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US - Oregon Permissible Exposure Limits (Z-1)	US TSCA Chemical Substance Inventory - Interim List of Active Substances
US - Pennsylvania - Hazardous Substance List	

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4) None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Titanium dioxide (airborne, unbound particles of respirable size), Carbon black (airborne, unbound particles of respirable size) Listed

National Inventory Status

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Y
Canada - NDSL	N (kaolin; propylene glycol; carbon black)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (kaolin)
Korea - KECI	Y
New Zealand - NZIoC	Υ
Philippines - PICCS	Y
USA - TSCA	Υ

Version No: 1.1

Everlife Waterborne Enamel High Gloss Medium Gray - F52113

Legend:

Y = All ingredients are on the inventory

N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	09/12/2018
Initial Date	09/13/2018

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

Ingredients with multiple cas numbers

Name	CAS No
kaolin	1332-58-7, 71888-52-3, 1026990-70-4, 12198-85-5, 12199-11-0, 190086-05-6, 290817-34-4, 384842-32-4, 39406-22-9, 52624-41-6, 849104-81-0, 903527-69-5, 90803-81-9, 944250-63-9, 95077-05-7
titanium dioxide (anatase)	1317-70-0, 13463-67-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chernwatch.

