FIXALL® SINCE 1883

F68101
FIXALL MULTI-SURFACE PATCH & REPAIR

TECHNICAL DATA SHEET

DESCRIPTION:

FixALL Multi-Surface Patch & Repair is a smooth ready-to-use repair compound formulated for filling, patching and sealing cracks, holes, gaps and surface imperfections on a wide variety of interior and exterior building materials. Its flexible elastomeric technology provides excellent adhesion while allowing the repair to accommodate normal substrate movement, helping reduce cracking and separation commonly associated with rigid patching materials. The durable, weather-resistant formula is ideal for repairs where flexibility, adhesion and long-term exterior durability are required

FEATURES AND BENEFITS:

- **Multi-Surface Adhesion –** Adheres to most surfaces that are clean and free of dust, dirt or chalk.
- **Flexibility –** Tested to 100% elongation and recovery without rupture of joints.
- **Sag Control –** Bonds rapidly when applied properly.
- **Flexible Elastomeric Technology –** Remains flexible after curing to accommodate normal substrate movement and help resist cracking.
- **Smooth Finish -** Smooth consistency spreads and tools easily with a putty knife, trowel or similar application tool.
- **Weather Resistant –** Resists deterioration from normal exposure to rain, moisture and changing weather conditions after fully cured and properly coated where required.

TECHNICAL DATA:

Color (Wet/Dry)	White
Base	Vinyl terpolymer
Consistency	Smooth paste
Weight per Gallon	Approximately 11.5 lbs/Gal (1.4 kg/L)
Weight Solids %	64% ±2
Drying Time	30 Minutes – 1 Hour depending on film thickness, temperature, and humidity
Paint/Recoat Time	30 Minutes – 1 Hour depending on film thickness, temperature, and humidity
Application Temperature	Minimum 50°F (10°C)
Cleanup	Warm, soapy water
Shelf Life	12 months in unopened container when stored at room temperature

TYPICAL USE

Multi-Surface Patch & Repair is intended for repairing cracks, holes, gaps, dents, chips and other surface imperfections on properly prepared:

- Concrete, Masonry, Stucco, Brick, Fiber Cement, Drywall, Plaster, Wood, Composite Board, Fiber Cement Primed Metal and previously painted surfaces

Multi-Surface Patch & Repair is suitable for applications such as:

- Wall & ceiling repairs, exterior siding repairs, trim repairs, masonry cracks, stucco repairs and transitions where two different surfaces meet

APPLICATION:

1. **Prepare Repair Area:** Remove loose material and slightly open narrow cracks where necessary to provide adequate surface area for adhesion.
2. **Apply Compound:** Using a flexible putty knife, trowel or similar tool, press the compound firmly into the repair area to ensure complete contact with the substrate.
3. **Smooth and Feather:** Smooth the repair and feather the edges into the surrounding surface. Avoid excessive tooling once the material begins to skin.
4. **Deep Repairs:** For deep holes, cracks or voids, apply in multiple layers rather than one excessively thick application. Allow each layer to dry sufficiently before applying additional material.
5. **Finishing:** Allow the repair to dry thoroughly before priming or painting. A lightly damp sponge or rag may be used when necessary to remove excess material to achieve the desired surface profile. Note: material must still be wet to smooth out and remove excess material.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

ICP Construction, Inc.
150 Dascomb Rd., Andover, MA 01810
866.667.5119 | www.icpgroup.com | H26

FIXALL®
SINCE 1883

F68101
FIXALL MULTI-SURFACE PATCH & REPAIR

TECHNICAL DATA SHEET

APPLICATION TOOLS

STORAGE & HANDLING PRECAUTIONS:

Store in a tightly closed container at room temperature. Protect from freezing and excessive heat. Dispose of empty containers in accordance with local regulations.

SAFETY INFORMATION:

Refer to the product's Safety Data Sheet (SDS) for detailed health and safety information. Use only with adequate ventilation. Avoid contact with eyes and prolonged skin exposure.

LIMITATIONS:

Not intended for expansion joints. Do not apply when temperatures are below 50°F. Multi-Surface Patch & Repair cannot be sanded. Excess material should be removed immediately or when the material is still wet, the use of a damp rag or sponge can be used.

Visit fixallpaint.com for additional products.

MADE IN THE USA WITH GLOBALLY SOURCED MATERIALS

ICP Construction, Inc.
150 Dascomb Rd., Andover, MA 01810
866.667.5119 | www.icpgroup.com | H26

ICP