

Ceramithane Matte - F82703

ICP Construction, Inc.

Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2024) requirements

Initial Date: 01/24/2017 Revision Date: 07/09/2025 Print Date: 07/09/2025

S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Ceramithane Matte - F82703
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses Finish for wood, primed metal and masonry floors and kitchen cabinetry

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction, Inc.				
Address	150 Dascomb Road Andover MA 01810 United States				
Telephone	-866-667-5199 1-978-623-9987				
Fax Not Available					
Website	www.icpgroup.com				
Email	sds@icpgroup.com				

Emergency phone number

~	
Association / Organisation	Chemtel
Emergency telephone number(s)	1-800-225-3924
Other emergency telephone number(s)	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Serious Eye Damage/Eye Irritation Category 2A, Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 3

Label elements

Hazard pictogram(s)





Signal word

Danger

Hazard statement(s)

H319	Causes serious eye irritation.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H402	Harmful to aquatic life.

 Version No: 1.1
 Page 2 of 10
 Initial Date: 01/24/2017

Ceramithane Matte - F82703

Revision Date: **07/09/2025**Print Date: **07/09/2025**

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.			
P260 Do not breathe mist/vapours/spray.				
P280 Wear protective gloves, protective clothing, eye protection and face protection.				
P273 Avoid release to the environment.				
P202 Do not handle until all safety precautions have been read and understood.				
P264	Wash all exposed external body areas thoroughly after handling.			

Precautionary statement(s) Response

P308+P313	posed or concerned: Get medical advice/ attention.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P314	Get medical advice/attention if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

Precautionary statement(s) Storage

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
107-21-1	1-5	ethylene glycol	
111109-77-4	1-5	dipropylene glycol dimethyl ether	
29911-28-2	3-7	dipropylene glycol mono-n-butyl ether - alpha isomer	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Version No: 1.1 Page 3 of 10

Ceramithane Matte - F82703

Initial Date: 01/24/2017 Revision Date: 07/09/2025 Print Date: 07/09/2025

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.

Fire/Explosion Hazard

other pyrolysis products typical of burning organic material.

May emit poisonous fumes

May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Mir	٦Or	Sr	\ill

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eves
- Control personal contact with the substance, by using protective equipment.
- **Major Spills**
- Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

The tendency of many ethers to form explosive peroxides is well documented. Ethers lacking non-methyl hydrogen atoms adjacent to the ether link are thought to be relatively safe

- DO NOT concentrate by evaporation, or evaporate extracts to dryness, as residues may contain explosive peroxides with DETONATION potential
- Any static discharge is also a source of hazard.

The substance accumulates peroxides which may become hazardous only if it evaporates or is distilled or otherwise treated to concentrate the peroxides. The substance may concentrate around the container opening for example.

Purchases of peroxidisable chemicals should be restricted to ensure that the chemical is used completely before it can become peroxidised.

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- ▶ DO NOT allow clothing wet with material to stay in contact with skin

Other information

Safe handling

Conditions for safe storage, including any incompatibilities

Suitable container

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

- Glycol ethers may form peroxides under certain conditions; the potential for peroxide formation is enhanced when these substances are used in processes such as distillation where they are concentrated or even evaporated to near-dryness or dryness; storage under a nitrogen atmosphere is recommended to minimise the possible formation of highly reactive peroxides
- Nitrogen blanketing is recommended if transported in containers at temperatures within 15 deg C of the flash-point and at or above the flash-point - large containers may first need to be purged and inerted with nitrogen prior to loading
- In the presence of strong bases or the salts of strong bases, at elevated temperatures, the potential exists for runaway reactions.
- Contact with aluminium should be avoided; release of hydrogen gas may result- glycol ethers will corrode scratched aluminium surfaces.
- May discolour in mild steel/copper; lined containers, glass or stainless steel is preferred
- Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid.
- Avoid reaction with oxidising agents















- Must not be stored together
- May be stored together with specific preventions

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Version No: 1.1 Page 4 of 10

Ceramithane Matte - F82703

Initial Date: 01/24/2017 Revision Date: 07/09/2025 Print Date: 07/09/2025

Source	Ingredient	Material name	TWA	STEL	Peak	Notes		
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D		
Emergency Limits								
Ingredient	TEEL-1		TEEL-2		TEEL-3			
ethylene glycol	30 ppm		150 ppm		900 ppm			
Ingredient	Original IDLH	Original IDLH Not Available						
ethylene glycol	Not Available				Not Available			
dipropylene glycol dimethyl ether	Not Available			Not Available				
dipropylene glycol mono-n-butyl ether - alpha isomer	Not Available	Not Available			Not Available			

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Individual protection measures, such as personal protective equipment











Eye and face protection

- Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- ► Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

Skin protection

See Hand protection below

Wear chemical protective gloves, e.g. PVC.

Hands/feet protection

▶ Wear safety footwear or safety gumboots, e.g. Rubber

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Body protection

See Other protection below

- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted.

Other protection

- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.
- Overalls.
- P.V.C apron
- Barrier cream.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Text		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available

Version No: 1.1 Page 5 of 10

Ceramithane Matte - F82703

Initial Date: **01/24/2017** Revision Date: **07/09/2025**

Print Date: **07/09/2025**

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

a) Acute Toxicity	Based on available data, the classification criteria are not met.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	There is sufficient evidence to classify this material as carcinogenic
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	There is sufficient evidence to classify this material as toxic to specific organs through repeated exposure
j) Aspiration Hazard	Based on available data, the classification criteria are not met.
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack
Ingestion	of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material causes serious eye irritation.
Chronic	Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems. There is sufficient evidence to suggest that this material directly causes cancer in humans. Some glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous.

Ceramithane Matte - F82703	TOXICITY	IRRITATION
Ceraminane Matte - 1 02703	Not Available	Not Available
ethylene glycol		i
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 9530 mg/kg ^[2] Eye (Rodent - rabbit): 0.012ppm/3D	
	Inhalation (Human) TCLo: 10000 mg/m3 ^[2]	Eye (Rodent - rabbit): 100mg/1H - Mild
	Inhalation (Rat) LC50: 50100 mg/m3/8 hr ^[2]	Eye (Rodent - rabbit): 1440mg/6H - Moderate

Version No: 1.1 Page 6 of 10

Ceramithane Matte - F82703

Initial Date: 01/24/2017 Revision Date: 07/09/2025

Print Date: 07/09/2025

	I		
	Oral (child) TDLo: 5500 mg/kg ^[2]	Eye (Rodent - rabbi	t): 500mg/24H - Mild
	Oral (Human)LDLo: 398 mg/kg ^[2] Eye (Rodent - rat): 0.012%/3D		
	Oral (Rat) LD50: 4700 mg/kg ^[2]	Oral (Rat) LD50: 4700 mg/kg ^[2] Eye: no adverse effect observed (not irritating) ^[1]	
		Skin (Rodent - rabb	it): 555mg - Mild
		Skin: no adverse eff	fect observed (not irritating) ^[1]
	TOXICITY		IRRITATION
dipropylene glycol dimethyl	dermal (rat) LD50: >2000 mg/kg ^[2]		Not Available
ether	Inhalation (Rat) LC50: >792 ppm4h ^[1]		
	Oral (Rat) LD50: 3300 mg/kg ^[2]		
	TOXICITY	IRRITATION	
dipropylene glycol mono-n-	dermal (rat) LD50: >2000 mg/kg ^[2]	Eye (Rodent - rabbit): 10	00mg
butyl ether - alpha isomer	Inhalation (Rat) LC50: >2.04 mg/l4h ^[2]	observed (not irritating) ^[1]	
	Oral (Mouse) LD50; 2160 mg/kg ^[2]	Skin: no adverse effect	observed (not irritating) ^[1]
Legend:	Value obtained from Europe ECHA Registered Suspecified data extracted from RTECS - Register of Technology		obtained from manufacturer's SDS. Unless otherwise
	<u> </u>		
ethylene glycol	[Estimated Lethal Dose (human) 100 ml; RTECS que cells. For ethylene glycol: Ethylene glycol is quickly and extensively absorbed through the airways; absorption through skin is appa	throughout the gastrointestinal tract	t. Limited information suggests that it is also absorbed
DIPROPYLENE GLYCOL DIMETHYL ETHER	In vitro mutagenicity studies were negative; animal mutagencity studies were negative * Dow MSDS The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
DIPROPYLENE GLYCOL DIMETHYL ETHER & DIPROPYLENE GLYCOL MONO-N-BUTYL ETHER - ALPHA ISOMER	For propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene gly methyl ether acetate (DPMA) and tripropylene glycol Testing of a wide variety of propylene glycol ethers h ethylene series. The common toxicities associated w effects on the reproductive organs, the developing etheropylene glycol ethers. In the ethylene series, meta	I methyl ether (TPM). nas shown that propylene glycol-bas vith the lower molecular weight hom mbryo and foetus, blood or thymus	sed ethers are less toxic than some ethers of the hologues of the ethylene series, such as adverse gland, are not seen with the commercial-grade
Acute Toxicity	×	Carcinogenicity	·
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eve			

Acute Toxicity	×	Carcinogenicity	✓
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	~	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	•
Mutagenicity	×	Aspiration Hazard	×

Legend:

X − Data either not available or does not fill the criteria for classification
✓ − Data available to make classification

SECTION 12 Ecological information

Toxicity

	-						
Ceramithane Matte - F82703	Endpoint	Test Duration (hr)		Species	Value		Source
Ceramithane Matte - F62703	Not Available	Not Available		Not Available	Not Avail	able	Not Available
	Endpoint	Test Duration (hr)	Specie	es		Value	Source
	EC50	48h	Crusta	cea		>100mg/l	2
ethylene glycol	EC50(ECx)	Not Available	Algae	or other aquatic plants		6500-7500mg/l	1
	EC50	96h	Algae	or other aquatic plants		6500-13000mg/	/ 1
	LC50	96h Fish			8050mg/L	4	
	Endpoint	Test Duration (hr)	Spe	ecies		Value	Source
lipropylene glycol dimethyl	EC50	72h	Alga	ae or other aquatic plar	nts	1746mg/l	2
ether	NOEC(ECx)	504h	Cru	stacea		10mg/l	2
	LC50	96h	Fish	1		106-111mg	y/l 2
		<u>'</u>				<u> </u>	
dipropylene glycol mono-n- butyl ether - alpha isomer	Endpoint	Test Duration (hr)	Sn.	ecies		Value	Source
butyi etilei - alpila isolilei	Liiupoiiit	rest buration (III)	Эþ	CUICO		value	Source

Version No: 1.1 Page 7 of 10

Ceramithane Matte - F82703

Initial Date: **01/24/2017** Revision Date: **07/09/2025**

Print Date: 07/09/2025

EC50	48h	Crustacea	>100mg/l	2
EC50	96h	Algae or other aquatic plants	519mg/l	2
NOEC(ECx)	48h	Crustacea	1000mg/l	1
LC50	96h	Fish	681.18mg/l	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Harmful to aquatic organisms.

For Propylene Glycol Ethers: log Kow's range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation. Henry's Law Constants are low for all category members, ranging from 5.7 x 10-9 atm-m3/mole for TPM to 2.7 x10-9 atm-m3/mole for PnB. For Glycol Ethers:

Environmental Fate: Several glycol ethers have been shown to biodegrade however; biodegradation slows as molecular weight increases. No glycol ethers that have been tested demonstrate marked resistance to biodegradative processes. No glycol ethers that have been tested demonstrate marked resistance to biodegradative processes.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)
dipropylene glycol dimethyl ether	HIGH	HIGH
dipropylene glycol mono-n-butyl ether - alpha isomer	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene glycol	LOW (BCF = 200)
dipropylene glycol dimethyl ether	LOW (LogKOW = 0.5)
dipropylene glycol mono-n-butyl ether - alpha isomer	LOW (LogKOW = 1.1274)

Mobility in soil

Ingredient	Mobility
ethylene glycol	HIGH (Log KOC = 1)
dipropylene glycol dimethyl ether	LOW (Log KOC = 10)
dipropylene glycol mono-n-butyl ether - alpha isomer	LOW (Log KOC = 10)

Other adverse effects

No evidence of ozone depleting properties were found in the current literature.

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

• If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).

SECTION 14 Transport information

Labels Required

zabolo Noquinou	
Marine Pollutant	NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

Version No: 1.1 Page 8 of 10

Ceramithane Matte - F82703

Initial Date: 01/24/2017 Revision Date: 07/09/2025 Print Date: 07/09/2025

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethylene glycol	Not Available
dipropylene glycol dimethyl ether	Not Available
dipropylene glycol mono-n-butyl ether - alpha isomer	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ethylene glycol	Not Available
dipropylene glycol dimethyl ether	Not Available
dipropylene glycol mono-n-butyl ether - alpha isomer	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US - New Jersey Right to Know Hazardous Substances

US - Pennsylvania - Hazardous Substance List

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US New York City Community Right-to-Know: List of Hazardous Substances

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

dipropylene glycol dimethyl ether is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - Pennsylvania - Hazardous Substance List

US New York City Community Right-to-Know: List of Hazardous Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Section 12(b) - List of Chemical Substances Subject to Export Notification Requirements

US TSCA Section 5(a)(2) - Significant New Use Rules (SNURs)

dipropylene glycol mono-n-butyl ether - alpha isomer is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - Pennsylvania - Hazardous Substance List

US New York City Community Right-to-Know: List of Hazardous Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	

Version No: 1.1 Page 9 of 10

Ceramithane Matte - F82703

Initial Date: 01/24/2017 Revision Date: 07/09/2025

Print Date: 07/09/2025

Combustible Dust	N-
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	
Specific target organ toxicity (single or repeated exposure)	
Aspiration Hazard	
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylene glycol	5000	2270

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

CAS No	%[weight]	Name
107-21-1	1-5	ethylene glycol
This information must be included in all SDSs that are copied and distributed for this material.		

Additional Federal Regulatory Information

Not Applicable

State Regulations

US. California Proposition 65



MARNING: This product can expose you to chemicals including ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Additional State Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ethylene glycol; dipropylene glycol dimethyl ether; dipropylene glycol mono-n-butyl ether - alpha isomer)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	No (dipropylene glycol dimethyl ether)
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	07/09/2025
Initial Date	01/24/2017

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit

Version No: 1.1 Page 10 of 10

Ceramithane Matte - F82703

Initial Date: 01/24/2017 Revision Date: 07/09/2025 Print Date: 07/09/2025

- ► IARC: International Agency for Research on Cancer
 ► ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit。
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure StandardOSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ► TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
 IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
 ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ► NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
 TCSI: Taiwan Chemical Substance Inventory
- ► INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.