

Waterborne Alkyd Stain Killer - F203 Series

Product Description

This interior quick drying white stain kill primer-sealer prevents the migration of multiple bleeding stains that show through other primers. This primer seals inactive water stains on plaster, ceiling tile and sheet rock. Soot damage and smoke residue that remains after washing or solvent cleaning can be sealed with this product prior to repainting.

Recommended Use

Sheetrock, plaster, wallboard, interior wood trim, primed metal.

General Surface Preparation

Surfaces to be primed must be clean, dry and free of contaminants such as dust, dirt, oil, grease, wax, loose paint, rust and mill scale. Mildew must be killed by scrubbing with an EPA Registered Mildew solution. Rinse with clean water and allow to dry.

Application

This product should be applied by brush, roller or spray. This material is supplied at proper application consistency. Use water and soap for easy cleanup of paint tools and equipment.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Plaster, Wallboard, Sheetrock, Primed Metal, Wood, Aluminum:
1 coat FixAll Low Odor Primer/Sealer/Stain Killer F20300
1 or 2 coats FixAll or California Latex or Alkyd finish

Precautions

Do not mix with other paints, solvents or colors in oil. Keep from freezing. Air and surface temperature must be no lower than 50°F during application and drying time.

Environmental Health and Safety Information

CAUTION! Keep out of reach of children. Do not take internally. Close container after each use.
FIRST AID: If swallowed, do not induce vomiting. Call physician immediately.

Waterborne Alkyd Stain Killer - F203 Series

*Based upon ASTM D6886 testing. Product meets or exceeds current OTC VOC standards (www.otcair.org). VOC testing performed on product formulation prior to application. The product may produce emissions and odors during application, curing and for some time afterwards. Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

Technical Data

Product Type	Primer
Exposure	Interior
Specular Gloss	4° ± 2
Volume Solids	42.2% ± 2
Weight Solids	57.5% ± 2
Vehicle Solids	21.1% ± 2
Pigment	34.5% ± 2
Wet Film Thickness	4.0 mils
Dry Film Thickness	2.1 mils
Viscosity @ 77 °F	97KU ± 2
Max VOC	100 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	400-500 s.f./gal.
Porous	200-275 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	30 minutes
To Handle	4 hours
To Recoat	2 hours
To Wash	N/A

(@ 70 - 77 °F, 50% R.H.)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" Nap Synthetic Fiber
Airless Spray	.017 to .019 Tip

Available Package Sizes

Gallon	Quart
--------	-------

(Weight Per Gallon: 11.4 lbs. ± .5 lb)

Available Colors and Bases

Available in 0 stock colors