

## Spackle Pro - F689 Series

### Product Description

Professional Grade Spackle® is the finest quality ready-to-use surfacing compound designed for filling interior and minor exterior surface imperfections in previously painted or primed plaster, wallboard and wood. It has excellent workability, long open time, dries fast, and sands easily to a smooth, paintable surface.

### Recommended Use

For interior use in filling holes, cracks, dents and gouges on plaster, wallboard, wood, masonry and painted metal.

### General Surface Preparation

Clean surface to be patched thoroughly. Remove all loose dirt, paint, plaster, wax, grease and dust. Lightly sand glossy surfaces. New or unpainted areas must be primed prior to application with a premium quality acrylic primer.

### Application

Apply with a broad knife (wide or narrow, depending on the size of the area being filled). Spread paste evenly, pressing into holes and cracks, and feathering out the edges. Deep cracks and holes may require more than one application.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Spackle Pro is designed to fill holes on interior wood metal, plaster wallboard and masonry.  
Apply liberally allowing Spackle Pro to exceed the surface imperfection.  
Allow to dry, sand and apply a second application.  
Allow 1 hour prior to coatings application.

### Precautions

Do not apply to exterior areas if rain or heavy dew is expected. Not recommended in areas subject to high moisture. Do not apply in temperatures below 50°F. Do not use as skim coat on exterior surfaces. Repair is only as good as the substrate it is applied to. Carefully inspect the area to be patched and determine if conditions and product are correct.

### Environmental Health and Safety Information

**Do not take internally. Close container after each use. KEEP OUT OF REACH OF CHILDREN.**

Do not apply to exterior areas if rain or heavy dew is expected. Not recommended in areas subject to high moisture. Do not apply in temperatures below 50°F. Do not use as skim coat on exterior surfaces. Repair is only as good as the substrate it is applied to. Carefully inspect the area to be patched and determine if conditions and product are correct.

## Spackle Pro - F689 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Lead Warning !** - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

Technical Data	
<b>Product Type</b>	Specialty
<b>Exposure</b>	Interior/ Exterior
<b>Specular Gloss</b>	N/A° ±
<b>Volume Solids</b>	73.6% ± 2
<b>Weight Solids</b>	
<b>Vehicle Solids</b>	
<b>Pigment</b>	
<b>Wet Film Thickness</b>	
<b>Dry Film Thickness</b>	
<b>Viscosity @ 77 °F</b>	
<b>Max VOC</b>	60 g/l
<b>Flash Point ° F</b>	N/A
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water
Surface Spread Rate	
<b>Smooth</b>	N/A s.f./gal.
<b>Porous</b>	N/A s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
<b>To Touch</b>	30 minutes
<b>To Handle</b>	1 hour
<b>To Recoat</b>	1 hour
<b>To Wash</b>	N/A
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 40°F to Under 90°F	
Tools & Equipments	
<b>Brush</b>	
<b>Roller</b>	
<b>Airless Spray</b>	Not Recommended
Available Package Sizes	
Gallon	Quart
<i>(Weight Per Gallon:14.91 lbs. ± .5 lb)</i>	
Available Colors and Bases	
Available in 1 stock colors	