

## Sanding Sealer - F823 Series

### Product Description

FIXALL SANDING WOOD SEALER is recommended as a first coat for new or stained interior wood surfaces such as doors, cabinets, paneling, and other wood trim. It dries fast, is very easy to sand, and provides excellent "holdout". SANDING WOOD SEALER dries like a lacquer but contains no lacquer solvents.

### Recommended Use

As a first coat on new or stained interior wood surfaces to receive a varnish topcoat.

### General Surface Preparation

The surface must be free of wax, dust, grease, oil, dirt and any old finish, and must be totally dry. Sand, or use a chemical stripper, to remove and strip old finishes. Sand wood smooth and remove any dust with a vacuum or a clean rag solvent dampened. If desired, paste wood filler and / or stain should be applied before SANDING WOOD SEALER.

### Application

Apply one or two coats of SANDING WOOD SEALER, let dry, and then lightly sand if necessary. Follow with one or two coats of varnish depending on the wear the surface is to receive.

Method of Application: Brush, paint pad or spray.

### Clean up

Clean tools and equipment with mineral spirits or turpentine. Do not use water on natural bristle or china bristle brushes.

### Architectural Specifications

New or Bare wood surfaces:  
1 coat FixAll Sanding Sealer #F82303

### Precautions

Use only when the surface and air temperature is above 40° F. Not for use on floors.

### Environmental Health and Safety Information

## Sanding Sealer - F823 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Lead Warning !** - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

**CAUTION!** Combustible Liquid: Keep away from heat and flame. Close container after each use. Use only with adequate ventilation. Wash thoroughly after handling. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. KEEP OUT OF REACH OF CHILDREN. Working with flammables and combustibles: Fire extinguishers, a safety shower, and fire blankets must be immediately available. Use only explosion-proof electrical equipment, including lighting. Do not leave any material or equipment unattended.

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery, recycling and disposal for regulations.

Place the rags in an empty metal container that has a tight metal lid such as a paint or stain can. Fill the container with water until the rags are submerged; Fill Place the metal lid tightly over the water soaked formerly combustible rags. Place lid tightly on container. Coontact local municipal offices for disposal directions. Never dump solvent down any household or external drains or in any open water.

### Technical Data

<b>Product Type</b>	Primer
<b>Exposure</b>	Interior
<b>Specular Gloss</b>	40-70° ±
<b>Volume Solids</b>	33% ± 2
<b>Weight Solids</b>	38% ± 2
<b>Vehicle Solids</b>	31% ± 1
<b>Pigment</b>	3.4% ± 1
<b>Wet Film Thickness</b>	2.6 - 2.9 mils
<b>Dry Film Thickness</b>	1.1 - 1.2 mils
<b>Viscosity @ 77 °F</b>	
<b>Max VOC</b>	550 g/l
<b>Flash Point ° F</b>	Combustible
<b>Thinner</b>	Mineral Spirits
<b>Clean - up</b>	Mineral Spirits

### Surface Spread Rate

<b>Smooth</b>	400-450 s.f./gal.
<b>Porous</b>	300-350 s.f./gal.

(Spray Application is 50% of above)

### Drying Times

<b>To Touch</b>	30 minutes
<b>To Handle</b>	1 hour
<b>To Recoat</b>	1 hour
<b>To Wash</b>	14 days

(@ 70 - 77 °F, 50% R.H)

### Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

### Storage Temperature

Store Between Over 40°F to Under 100°F

### Tools & Equipments

<b>Brush</b>	China Bristle
<b>Roller</b>	Short Nap Synthetic or Natural
<b>Airless Spray</b>	.015 to .018 Tip / 40-60° angles

### Available Package Sizes

Gallon	Quart
(Weight Per Gallon:10.0 lbs. ± .5 lb)	

### Available Colors and Bases

Available in 1 stock colors

## Sanding Sealer - F823 Series

### Notes