

## Acrylic Stain Killer - F524 Series

### Product Description

FixAll Acrylic Stain Killer is a quick drying, high performance 100% acrylic latex stain blocking primer that provides exceptional adhesion and stain blocking properties. This application friendly, highly effective product may be used interior or exterior to block most bleeding type stains, seal porous surfaces and provide adhesion to hard and glossy surfaces.

### Recommended Use

Wallboard, Plaster, Sheetrock, Concrete, Masonry, Wood, Aluminum, Galvanized Metal, Plastic Laminates, Vinyl Wall Coverings, Previously Painted Surfaces

### General Surface Preparation

Surfaces to be primed must be clean, dry, and free of grease, oil, wax, rust, loose paint, mildew or any surface contaminants. Wash glue size off plaster or other surfaces from which wallpaper has been removed. Do not sand plaster until after the surface is primed. Tape joints on sheetrock should be sanded smooth, with care being exercised not to abrade the surrounding paper backing.

Stains: FixAll 100% Acrylic Stain Block hides well to seal many common stains such as crayon, graffiti, greasy spots, water stains, rust, smoke stains, cedar and redwood bleed. Before priming stained areas, remove as much of the stain as possible by washing, sanding or scraping. Some stains may require two coats. If an active stain discolors this primer, apply the finish coat to a small area to see if the stain is "locked" into the primer. If not, re-prime. When re-priming over heavy cedar bleed, wait 4-6 hours to ensure cedar bleed is locked into the primer.

Plasticizers must be thoroughly removed from vinyl wall coverings with mineral spirits, proper ventilation and a clean cloth that is changed frequently.

### Application

Material is supplied ready to use but can be thinned sparingly with water for proper application consistency. Do not brush out excessively but remove any sags or runs before material has started to dry. To hold back bleeding on heavily stained areas, a second coat of primer may be necessary.

Sanding of hard or glossy surfaces will increase adhesion of this product.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Plaster, Wallboard, Sheetrock, Concrete, Masonry, Galvanized Metal Wood, Aluminum:

1 coat FixAll Acrylic Stain Killer F52400

2 coats any California® or FixAll Latex, Alkyd or Urethane in desired finish.

### Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Difficult stains may require the use of FixAll Alkyd Stain Killer F20400.

### Environmental Health and Safety Information

**Keep out of reach of children. Do not take internally. Close container after each use.**

**Refer to Safety Data Sheet for additional health and safety information.**

Do not put in service until 24 hours after the last coat. Areas with heavy Cedar bleed may require and additional coat. Wait 4-6

## Acrylic Stain Killer - F524 Series

hours before applying a second coat over heavy cedar bleed areas.

## Acrylic Stain Killer - F524 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: [www.osha.gov/dsg/topics/silicacrystalline](http://www.osha.gov/dsg/topics/silicacrystalline).

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

FIRST AID: In case of eye contact, flush immediately with water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. If swallowed, rinse mouth with water (only if person is conscious). Call for medical assistance immediately. Do not induce vomiting unless directed to do so by medical professional.

WARNING! Use only with adequate ventilation. Do not breathe spray or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable

Technical Data	
Product Type	Primer
Exposure	Interior/ Exterior
Specular Gloss	15° ± 5
Volume Solids	37.9% ± 2
Weight Solids	51% ± 2
Vehicle Solids	55.8% ± 2
Pigment	44.2% ± 2
Wet Film Thickness	3.0 mils
Dry Film Thickness	1 mils
Viscosity @ 77 °F	98KU ± 5
Max VOC	100 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water
Surface Spread Rate	
Smooth	350-400 s.f./gal.
Porous	200-250 s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
To Touch	30 minutes
To Handle	4 hours
To Recoat	4 - 6 hours
To Wash	
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 40°F to Under 100°F	
Tools & Equipments	
Brush	Synthetic, Nylon or Polyester
Roller	3/4" Nap Synthetic Fiber
Airless Spray	
Available Package Sizes	
5 Gallon	Gallon
<i>(Weight Per Gallon:10.59 lbs. ± .5 lb)</i>	
Available Colors and Bases	
White	
Available in 0 stock colors	

## Acrylic Stain Killer - F524 Series

Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

Specific primers are recommended for certain new woods, rusted and other unique substrate conditions.