

Everlife Waterborne Enamel Satin - F100 Series

Product Description

Everlife Waterborne Enamel Satin is especially designed for use on interior and exterior surfaces. The tough, durable latex film can be lightly walked upon in about 4 hours after painting. Its excellent adhesion, toughness and resistance to alkalinity makes this an ideal all-purpose floor finish. Due to its resilient finish, Everlife is also ideal for use on walls and trim. Permits installation of tile and other floor covering materials directly over it.

Recommended Use

Ideal for inside or outside application over new or old wood and masonry surfaces such as patios, cellar floors, playrooms, porches, stairways, etc. and walls, trim and objects where a durable finish is desired.

General Surface Preparation

Surfaces must be thoroughly cleaned of all dirt and dust. Dirty surfaces should be washed with a strong detergent solution, rinsed with clean water and allowed to dry overnight. Grease, oils and wax should be removed by solvent cleaning to insure proper adhesion of the finish paint. All old, loose, scaly or flaking paint must be removed back to a sound substrate before any repainting is attempted. New concrete should be allowed to cure a minimum of 30 days before applying any finish. Steel troweled, hard, glassy smooth, and sealed concrete (curing agents or sealers) should be mechanically abraded or acid etched to create a profile to obtain proper adhesion. Water droplets should immediately penetrate into concrete to determine if coating is possible. New, dusty or chalky concrete should have a coat of FixAll Masonry Conditioner F70003 applied before Everlife is used as a finish. Everlife Satin is self-priming over unfinished wood and does not require a wood primer.

Application

Material is supplied ready to use but can be thinned up to one pint per gallon with water for first coat on new surfaces or for spot-priming bare areas on old finishes. Finish coat should be applied full body.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Wood, Floors:

2 coats FixAll Everlife Satin Acrylic F100xx

Masonry, Concrete, Patios, Breezeways, Steps:

2 coats FixAll Everlife Satin Acrylic F100xx (thin first coat 10-20% with water)

Walls:

2 coats FixAll Everlife Satin Acrylic F100xx

Repaint:

2 coats FixAll Everlife Satin Acrylic F100xx

Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Do not use in place of House Paint. For maximum rust inhibiting requirements prime bare ferrous metal with FixAll Everlife Metal Primers.

Environmental Health and Safety Information

KEEP OUT OF REACH OF CHILDREN. Do not take internally. Close container after each use.

Everlife Waterborne Enamel Satin - F100 Series

Product is ready to use from the container.

Everlife Waterborne Enamel Satin - F100 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: www.osha.gov/dsg/topics/silicacrystalline.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

All floor coatings are more slippery when the surface becomes wet or contaminated by dirt, oils, food, or beverage residues, or other debris. To help reduce the possibility of slipping on a dry, clean floor, add Slip Resistant Additive F09098 before application. To attain the best possible skid resistance, coated areas must be kept dry, properly cleaned and maintained.

FIRST AID: In case of eye contact, flush immediately with water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. If swallowed, rinse mouth with water (only if person is conscious). Call for medical assistance immediately. Do not induce vomiting unless directed to do so by medical professional.

WARNING! Use only with adequate ventilation. Do not breathe spray or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow

Technical Data

Product Type	Finish
Exposure	Interior/ Exterior
Specular Gloss	30° ± 5
Volume Solids	36% ± 2
Weight Solids	52% ± 2
Vehicle Solids	43% ± 2
Pigment	57% ± 2
Wet Film Thickness	4.0 mils
Dry Film Thickness	1.4 mils
Viscosity @ 77 °F	97KU ± 3
Max VOC	100 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	400-450 s.f./gal.
Porous	250-300 s.f./gal.
<i>(Spray Application is 50% of above)</i>	

Drying Times

To Touch	1 hour
To Handle	12 hours
To Recoat	4 hours
To Wash	14 days
<i>(@ 70 - 77 °F, 50% R.H)</i>	

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" - 1/2" Nap
Airless Spray	.017 to .019 Tip

Available Package Sizes

5 Gallon	Quart
Gallon	
<i>(Weight Per Gallon:11.01 lbs. ± .5 lb)</i>	

Available Colors and Bases

Pastel Base	Medium Base
Deep Base	Neutral Base
Available in 8 stock colors	

Everlife Waterborne Enamel Satin - F100 Series

respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. The manufacturer or re-seller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.

This product is self-priming over multiple new and previously painted surfaces. Specific primers are recommended for new wood, stained and other unique substrate conditions.