

## 6-In-1 Primer & Sealer - F320 Series

### Product Description

FixAll<sup>®</sup> 6-In-1 Primer & Sealer is a fast-drying, high-performance, 100% acrylic latex primer engineered for both interior and exterior applications where superior adhesion, surface sealing, and stain control are required. This versatile, multi-purpose primer is formulated to bond tightly to a wide range of substrates, including difficult-to-coat and previously painted glossy surfaces, while creating a uniform, receptive base for subsequent topcoats.

### Recommended Use

For properly prepared wallboard, plaster, sheetrock, masonry, wood, concrete, galvanized metal, plastic laminates, vinyl wall coverings, under wallcoverings as well as previously painted surfaces.

### General Surface Preparation

Surfaces to be primed must be clean, dry, and free of grease, oil, wax, rust, loose paint, mildew or any surface contaminants. Wash glue size off plaster or other surfaces from which wallpaper has been removed.

Do not apply over calcimine or other water soluble paints. Fill nicks, holes and voids with Spackle, sand smooth and remove dust. New plaster and masonry surfaces must be fully cured before priming. Wash new plaster with clean water, rinsing rags or sponges frequently. Do not sand plaster until after the surface is primed. Tape joints on sheet rock should be sanded smooth, with care being exercised not to abrade the surrounding paper backing. Wire brush rusted areas to remove loose rust. Plasticizes must be thoroughly removed from vinyl wallcoverings with mineral spirits and a clean cloth that is changed frequently.

Sanding will increase adhesion on cleaned hard or glossy surfaces.

6-In-1 Primer & Sealer hides well to seal many common stains. Before priming stained areas, remove as much of the stain as possible by washing, sanding or scraping. Some stains may require two coats. If an active stain discolors this primer, apply the finish coat to a small area to see if the stain is "locked" into the primer. If not, re-prime.

### Application

Stir thoroughly before use.

6-In-1 Primer & Sealer is ready-to-use as it comes from the container.

For best results, apply full even coats and work to a wet edge. Avoid excessive brushing or rolling. Application on hard non-porous surfaces requires a minimum of 2 hours dry time before re-coating. Stearate containing clear finishes, shellacs and any clear finish that has been waxed, polished or has surface soap residue can present adhesion problems for any coating. Apply a test area of primer over any clear finish and test for adequate adhesion after one week of curing.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Plaster, Wallboard, Sheetrock, Concrete, Composites, Hardboard, Masonry, Ferrous Metal-Primed, Galvanized Metal, Wood, Aluminum:

1 coat 6-In-1 Primer & Sealer F320

### Precautions

### Environmental Health and Safety Information

"Keep out of reach of children. Do not take internally. Close container after each use.  
Refer to Safety Data Sheet for additional health and safety information."

## 6-In-1 Primer &amp; Sealer - F320 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**FIRST AID:** In case of eye contact, flush immediately with water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. If swallowed, rinse mouth with water (only if person is conscious). Call for medical assistance immediately. Do not induce vomiting unless directed to do so by medical professional.

**WARNING!** Use only with adequate ventilation. Do not breathe spray or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

## Notes

Technical Data	
<b>Product Type</b>	Primer
<b>Exposure</b>	Interior/ Exterior
<b>Specular Gloss</b>	10° ± 5
<b>Volume Solids</b>	30% ± 2
<b>Weight Solids</b>	44% ± 2
<b>Vehicle Solids</b>	75% ± 2
<b>Pigment</b>	25% ± 2
<b>Wet Film Thickness</b>	4.5 mils
<b>Dry Film Thickness</b>	1.5 mils
<b>Viscosity @ 77 °F</b>	95KU ± 5
<b>Max VOC</b>	100 g/l
<b>Flash Point °F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water
Surface Spread Rate	
<b>Smooth</b>	400-450 s.f./gal.
<b>Porous</b>	300-350 s.f./gal.
(Spray Application is 50% of above)	
Drying Times	
<b>To Touch</b>	30 Minutes
<b>To Handle</b>	4 Hours
<b>To Recoat</b>	2 Hours
<b>To Wash</b>	N/A
(@ 70 - 77 °F, 50% R.H.)	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 50°F to Under 100°F	
Tools & Equipments	
<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" - 1/2" Nap
<b>Airless Spray</b>	.017 to .019 Tip
Available Package Sizes	
5 Gallon	Gallon
Quart	
(Weight Per Gallon:10.4 lbs. ± .5 lb)	
Available Colors and Bases	
White	
Available in 0 stock colors	