

## Mason-Cote 100% Acrylic Latex Block Filler - F375 Series

### Product Description

Mason-Cote Block Filler is a high quality exterior acrylic block filler formulated to fill small imperfections and pinholes in masonry block and porous concrete before topcoating. This product contains mineral type fillers and fine silica aggregates which fill voids and prevent seepage from driving rains and snow. This 100% acrylic block filler is easy to apply, alkali resistant and provides a uniform surface capable of receiving all types of finish coats. Mason-Cote Block Filler is not water sensitive after application and its inherent flexibility gives it the finest characteristics available in an exterior block filler, far superior to cementitious and PVA block fillers.

### Recommended Use

Masonry block, concrete, brick, stone

### General Surface Preparation

Nibs and mortar joints should be "bricked down" to remove all protrusions and mortar splatters. All dirt, grease, oil and other contaminants should be removed by brushing or solvent washing.

### Application

Mason-Cote Block Filler is supplied ready to use and can be applied by brush or roller. Spray application is not recommended because the silica content is somewhat abrasive to spray equipment. Maximum block filling qualities are achieved with use of a roller (1/2" in nap or longer). Mason-Cote Block Filler should be applied full body vertically and cross hatched horizontally to remove all roller ridges and unevenness in the block filler. Brushing should be done with a short stubby brush, working the material well into the pinholes, pores and voids. Material should be applied in horizontal sections with the block mortar lines serving as a guide.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

CONCRETE BLOCK, MASONRY  
 1 coat Mason-Cote Block Filler  
 1 or 2 coats California Acrylic Latex, Alkyd, Urethane or Epoxy

### Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing.

### Environmental Health and Safety Information

**Keep out of reach of children. Do not take internally. Close container after each use.**

## Mason-Cote 100% Acrylic Latex Block Filler - F375 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: [www.osha.gov/dsg/topics/silicacrystalline](http://www.osha.gov/dsg/topics/silicacrystalline).

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

Technical Data	
<b>Product Type</b>	Industrial
<b>Exposure</b>	Interior/ Exterior
<b>Specular Gloss</b>	60° ± 2
<b>Volume Solids</b>	47.6% ± 2
<b>Weight Solids</b>	66.9% ± 2
<b>Vehicle Solids</b>	44.1% ± 2
<b>Pigment</b>	55.9% ± 2
<b>Wet Film Thickness</b>	8.5 mils
<b>Dry Film Thickness</b>	3.8 mils
<b>Viscosity @ 77 °F</b>	112KU ± 5
<b>Max VOC</b>	100 g/l
<b>Flash Point ° F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water
Surface Spread Rate	
<b>Smooth</b>	250-300 s.f./gal.
<b>Porous</b>	150-200 s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
<b>To Touch</b>	4-6 hours
<b>To Handle</b>	16 hours
<b>To Recoat</b>	24 hours
<b>To Wash</b>	N/A
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Maximum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 40°F to Under 100°F	
Tools & Equipments	
<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" -3/4" Nap Synthetic Fiber
<b>Airless Spray</b>	Not Recommended
Available Package Sizes	
5 Gallon	
<i>(Weight Per Gallon:13.2 lbs. ± .5 lb)</i>	
Available Colors and Bases	
Available in 0 stock colors	