

Everlife Waterborne Enamel High Gloss - F521 Series

Product Description

This durable 100% acrylic, ceramic reinforced waterborne enamel provides a durable High Gloss finish for many general maintenance requirements. It provides superior color retention and moisture resistance when used exterior and is rust inhibiting when applied in the proper system.

*Note F52104 Wrought Iron Black is available as a Low Luster only.

Recommended Use

Concrete, wood, wallboard, masonry block, plaster, primed metal.

General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, and other surface contamination. Patch irregularities using Spackle patching paste or an appropriate patching compound.

New Plaster - Knife off all nibs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

Wallboard, Sheetrock, Gypsum Board - Joint compound should be sanded smooth, but avoid abrading the paper.

Ferrous Metal - Clean, then prime with FixAll Rust-inhibiting Latex primer

Wood - Seal knots and stains with FixAll Alkyd Stain Killer F20400.

Masonry Block - Apply one coat of a masonry block filler if a denser surface is desired #F51500.

Previously Painted Surfaces - Wash, sand or dust to obtain a paintable surface.

Glossy Surfaces - Dull by sanding to insure proper adhesion of paint.

Application

This product is ready-to-use as it comes from the container, but can be thinned sparingly with water if necessary. Air and surface temperatures should be 50°F (10°C) or higher during application and drying time.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Plaster, Wallboard, Sheetrock, Concrete, Non-Porous Masonry:

- 1 Coat FixAll F50600 Universal Acrylic Primer
- 2 coats Everlife™ 100% Acrylic High Gloss Waterborne Enamel F521XX

Porous Masonry and Block:

- 1 coat of Latex Block Filler F51500
- 2 coats Everlife™ 100% Acrylic High Gloss Waterborne Enamel F521XX

Ferrous Metal - Unprimed:

- 1 coat FixAll Alkyd Primer F500xx or Novus Rust Stop Latex Primer F106xx
- 2 coats Everlife™ 100% Acrylic High Gloss Waterborne Enamel F521XX

Ferrous Metal - Primed - Galvanized Metal:

- 2 coats Everlife™ 100% Acrylic High Gloss Waterborne Enamel F521XX

Wood:

- 1 Coat FixAll F50600 Universal Acrylic Primer
- 2 coats Everlife™ 100% Acrylic High Gloss Waterborne Enamel F521XX

Precautions

Everlife Waterborne Enamel High Gloss - F521 Series

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Do not use in place of House Paint. For maximum rust inhibiting requirements prime bare ferrous metal with FixAll Everlife Metal Primers.

Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use.

Do not apply exterior when moisture or dew is expected within 24 hours. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor.

Everlife Waterborne Enamel High Gloss - F521 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: www.osha.gov/dsg/topics/silicacrystalline.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

FIRST AID: In case of eye contact, flush immediately with water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, seek medical attention immediately. If swallowed, rinse mouth with water (only if person is conscious). Call for medical assistance immediately. Do not induce vomiting unless directed to do so by medical professional.

WARNING! Use only with adequate ventilation. Do not breathe spray or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable

Technical Data

Product Type	Finish
Exposure	Interior/ Exterior
Specular Gloss	70° ± 5
Volume Solids	36% ± 2
Weight Solids	47% ± 2
Vehicle Solids	58% ± 2
Pigment	42% ± 2
Wet Film Thickness	3.0 mils
Dry Film Thickness	1.5 mils
Viscosity @ 77 °F	97KU ± 3
Max VOC	100 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	350-425 s.f./gal.
Porous	300-350 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	1 hour
To Handle	16 hours
To Recoat	3 hours
To Wash	14 Day Minimum

(@ 70 - 77 °F, 50% R.H)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" Nap Synthetic Fiber
Airless Spray	.017 to .019 Tip

Available Package Sizes

(Weight Per Gallon:10.18 lbs. ± .5 lb)

Available Colors and Bases

Pastel Base	Medium Base
Deep Base	Neutral Base
White	

Available in 8 stock colors

Everlife Waterborne Enamel High Gloss - F521 Series

Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. The manufacturer or reseller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.