

Kitchen & Bath Enamel Satin - F526 Series

Product Description

FixAll Kitchen and Bath Enamel is an extremely durable, 100% acrylic finish developed to withstand the moist, humid conditions in bathrooms and kitchens. The anti-spatter formulation flows easily, hides well, and contains an anti-microbial for outstanding mildew resistance on the film surface.

Recommended Use

Plaster, Sheetrock, Wallboard, Concrete & Masonry block, Wood, Primed Metal, Galvanized Metal.
 Wall and trim surfaces in kitchens, bathrooms and laundry rooms and alike.

General Surface Preparation

Surfaces to be painted must be free of dust, mildew, dirt, grease, wax, loose paint, or any other contaminant that may inhibit good adhesion. Lightly sand any hard or glossy surfaces to promote good adhesion. Repair cracks and imperfections with Muralo Spackle.

Application

Apply at temperatures above 50° F using a suitable brush, roller or spray.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Plaster, Wallboard, Sheetrock:
 1 coat FixAll Universal Primer F506xx
 2 coats Kitchen & Bath Enamel F52611
 Concrete, Masonry block:
 1 coat FixAll Universal Primer F506xx
 2 coats Kitchen & Bath Enamel F52611
 Porous Masonry and Block:
 1 coat Mason-Cote® Block Filler 3751
 2 coats Kitchen & Bath Enamel F52611
 Ferrous Metal - Un-primed:
 1 coat FixAll Rust Stop DTM Acrylic Latex Metal Primer 106xx
 2 coats Kitchen & Bath Enamel F52611

Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Use adequate ventilation.

Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use. Protect from freezing.

Keep from freezing. Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Use adequate ventilation.

Kitchen & Bath Enamel Satin - F526 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Mold / Mildew Statement : Contains an additive designed to inhibit growth of mold and mildew on the dried paint film only.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

Technical Data

Product Type	Finish
Exposure	Interior
Specular Gloss	23° ± 5
Volume Solids	36.8% ± 2
Weight Solids	50.4% ± 2
Vehicle Solids	74.7% ± 2
Pigment	25.3% ± 2
Wet Film Thickness	4.0 mils
Dry Film Thickness	1.6 mils
Viscosity @ 77 °F	103KU ± 3
Max VOC	150 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	350-400 s.f./gal.
Porous	250-300 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	1 hour
To Handle	6 hours
To Recoat	4 hours
To Wash	14 days

(@ 70 - 77 °F, 50% R.H.)

Surface Temperature At Application

Maximum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" Nap Synthetic Fiber
Airless Spray	.017 to .019 Tip

Available Package Sizes

Gallon	Quart
(Weight Per Gallon:10.6 lbs. ± .5 lb)	

Available Colors and Bases

Tintable White	
Available in 0 stock colors	