

WearAll Acrylic Enamel Satin - F528 Series

Product Description

This durable, easily applied acrylic enamel is designed to provide maximum performance in a satin water-based floor, wall and trim finish. It incorporates color retention, breathability, alkali, water and blister resistance and adhesion into its acrylic formulation.

Recommended Use

Floors, patios, porches, steps, decks, playrooms, basements, wood, concrete and masonry. Walls and trim where durability and abrasion resistance is required.

General Surface Preparation

Surface Preparation: Surfaces must be thoroughly cleaned of all dirt and dust. Dirty surfaces should be washed with a strong detergent solution, rinsed with clean water and allowed to dry overnight. Grease, oils and wax be removed by solvent cleaning to insure proper adhesion of the finish paint. All old, loose, scaly or flaking paint must be removed back to a sound substrate before any repainting is attempted. New concrete should be allowed to cure a minimum of 30 days before applying any finish. Steel trowelled, hard or glassy smooth concrete should be mechanically abraded to obtain proper adhesion. Curing agents or concrete hardeners can prevent adhesion of any coating unless the surface is mechanically abraded. Under normal conditions acid etching is not recommended but new dusty or chalky concrete should have a coat of FixAll Masonry Conditioner applied before Wear-All is used as a finish.

Wear-All is self-priming over unfinished wood and does not require a wood primer.

Application

Material is supplied ready to use but can be thinned up to one pint per gallon with water for first coat on new surfaces or for spot - priming bare areas on old finishes. Finish coat should be applied full body.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Wood, Floors:

2 coats California Wear-All Multi-Purpose Acrylic Latex Enamel F528XX

Concrete, Patios, Breezeways, Steps:

1 coat Stonite® Acrylic Masonry Conditioner F70003 as necessary

1 or 2 coats California Wear-All Multi-Purpose Acrylic Latex Enamel F528XX
(thin first coat 10-20% with water)

Dados, Walls:

2 coats California Wear-All Multi-Purpose Acrylic Latex Enamel F528XX

Repaint:

1 coat California Wear-All Multi-Purpose Acrylic Latex Enamel F528XX

Note: Wear-All Multi-Purpose Acrylic Latex Enamel can be patched and traffic areas relocated with less difficulty than any other floor finish.

Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from

WearAll Acrylic Enamel Satin - F528 Series

freezing. Use adequate ventilation.

Do not use on garage floors. Hot tires or the weight of a vehicle can cause loss of adhesion.

Do not apply over water, glass or other silicate concrete hardeners.

Not recommended on areas utilizing heavy duty lift trucks. Everlife® Urethane Enamel is a better finish for these areas.

Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use.

WearAll Acrylic Enamel Satin - F528 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

All floor coatings are more slippery when the surface becomes wet or contaminated by dirt, oils, food, or beverage residues, or other debris. To help reduce the possibility of slipping on a dry, clean floor, add Slip Resistant Additive F09098 before application. To attain the best possible skid resistance, coated areas must be kept dry, properly cleaned and maintained.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

Technical Data

Product Type	Finish
Exposure	Interior/ Exterior
Specular Gloss	18° ± 4
Volume Solids	31.8% ± 2
Weight Solids	45.4% ± 2
Vehicle Solids	75.3% ± 2
Pigment	24.7% ± 2
Wet Film Thickness	4 mils
Dry Film Thickness	1.2 mils
Viscosity @ 77 °F	95KU ± 5
Max VOC	150 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	400-450 s.f./gal.
Porous	275-325 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	1 hour
To Handle	16 hours
To Recoat	4 hours
To Wash	14 days

(@ 70 - 77 °F, 50% R.H)

Surface Temperature At Application

Maximum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 35°F to Under 118°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" Nap Synthetic Fiber
Airless Spray	.017 to .019 Tip

Available Package Sizes

5 Gallon	Quart
Gallon	

(Weight Per Gallon:10.5 lbs. ± .5 lb)

Available Colors and Bases

Pastel Base	Medium Base
Deep Base	Neutral Base

Available in 8 stock colors

WearAll Acrylic Enamel Satin - F528 Series