

Sportmans Camouflage Exterior Paint Flat - F555 Series

Product Description

FixAll Sportman's collection is a latex camouflage coating designed to provide excellent visual deception. Its light absorbing flat finish is designed for the finest performance in non-glare, non-reflection coatings. It dries quick and handles in just hours.

Recommended Use

Deer Stands, Duck Blinds, Sheds and other structures designed to blend into nature's backdrop.

General Surface Preparation

Surfaces must be clean and free of surface contaminants. On previously painted surfaces, remove all loose or scaly paint by sanding or scraping so that all remaining paint is tightly adhered to the surface. Fill all of the holes and joints around windows, doors, trim, clapboards and other openings appropriately with exterior Spackle or caulking compound. Spot prime on all bare spots or badly eroded areas with CalPro Latex or Oil Primer.

Mildewed areas should be cleaned with an EPA registered mildew solution. For protection use rubber gloves and safety goggles. Rinse with clean water and allow to dry before painting. In areas of excessive chalk, salt or dust, areas should be cleaned with pressure or scrubbed, then rinsed clean.

Application

Sportsmans Camouflage Exterior Flat is designed to be applied with a good quality paint applicator. Spot prime bare areas. Apply one or two coats to a properly prepared surface

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

New Wood, Clapboards, Shingles, Shakes, Trim:

- 1 Coat California CalPro Exterior Oil Primer 23100 or Calpro 100% Acrylic Latex Primer 46100
- 2 coats FixAll Acrylic Latex Camouflage Flat Paint F555XX

New Stucco, Masonry or Cement Asbestos:

- 2 coats FixAll Acrylic Latex Camouflage Flat Paint F555XX

Masonry Block, Porous Concrete:

- 1 coat FixAll Block Filler F37500
- 2 coats FixAll Acrylic Latex Camouflage Flat Paint F555XX

New Galvanized Metal (Downspouts, Facias, Gutters):

- 2 coats FixAll Acrylic Latex Camouflage Flat Paint F555XX

Wood-Repaint:

- 2 coats FixAll Acrylic Latex Camouflage Flat Paint F555XX

Precautions

Environmental Health and Safety Information

Keep away and out of reach from children. Do not take internally. Close container tightly after each use.

Do not paint when dew or moisture is imminent or temperatures expect to be below 35°F in the next 24 hours

Sportmans Camouflage Exterior Paint Flat - F555 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

| Technical Data | |
|---|-------------------------------|
| Product Type | Finish |
| Exposure | Exterior |
| Specular Gloss | 3° ± 5 |
| Volume Solids | 27% ± 2 |
| Weight Solids | 46% ± 2 |
| Vehicle Solids | 4.6% ± 1 |
| Pigment | 41% ± 2 |
| Wet Film Thickness | 4 mils |
| Dry Film Thickness | 1 mils |
| Viscosity @ 77 °F | 95KU ± 5 |
| Max VOC | 100 g/l |
| Flash Point ° F | Non-Combustible |
| Thinner | Water |
| Clean - up | Soap & Water |
| Surface Spread Rate | |
| Smooth | 350-400 s.f./gal. |
| Porous | 250-300 s.f./gal. |
| <i>(Spray Application is 50% of above)</i> | |
| Drying Times | |
| To Touch | 1 hour |
| To Handle | 8 hours |
| To Recoat | 4 hours |
| To Wash | 14 days |
| <i>(@ 70 - 77 °F, 50% R.H.)</i> | |
| Surface Temperature At Application | |
| Minimum: Over 50°F | Maximum: Under 90°F |
| Storage Temperature | |
| Store Between Over 40°F to Under 100°F | |
| Tools & Equipments | |
| Brush | Synthetic, Nylon or Polyester |
| Roller | 3/8" - 1/2" Nap |
| Airless Spray | .017 to .019 Tip |
| Available Package Sizes | |
| Gallon | |
| <i>(Weight Per Gallon:10.35 lbs. ± .5 lb)</i> | |
| Available Colors and Bases | |
| Available in 1 stock colors | |