

Fix-Rite Structure & Farm Exterior Alkyd Paint Semi Gloss - F666 Series

Product Description

Fix-Rite Structure & Farm Exterior Alkyd Paint is designed to provide long lasting rust inhibitive protection, at an economical price. Excellent for farm, home and industrial use. It covers well, has good adhesion and spreads further than other more expensive paints. Its dried paint film is non-toxic to farm livestock.

Recommended Use

Exterior Metal and Wood Surfaces

General Surface Preparation

Surfaces must be clean and free of surface contaminants. On previously painted surfaces, remove all loose or scaly paint by sanding or scraping so that all remaining paint is tightly adhered to the surface. Fill all of the holes and joints around windows, doors, trim, clapboards and other openings appropriately with exterior Spackle or caulking compound. Spot prime on all bare spots or badly eroded areas with CalPro Latex or Oil Primer.

Rusty metal must be abraded to remove scaling rust.

Mildewed areas should be cleaned with an EPA registered mildew solution. For protection use rubber gloves and safety goggles. Rinse with clean water and allow to dry before painting. In areas of excessive chalk, salt or dust, areas should be cleaned with pressure or scrubbed, then rinsed clean.

Application

BARN, FENCE & ROOF PAINT is designed to be applied with a good quality paint applicator. Spot prime bare areas. Apply one or two coats to a properly prepared surface. Allow a minimum of 24 hours between coats. Spread paint evenly and thoroughly brush out. Do not over apply. Too heavy of a coat will result in sagging and drying problems. Avoid applying paint in direct sunlight.

Clean up

Clean tools and equipment with mineral spirits or turpentine. Do not use water on natural bristle or china bristle brushes.

Architectural Specifications

Ferrous Metal - Un-primed:

- 1 coat Rust Inhibiting Metal Primer
- 1 or 2 coats FixAll Fix Rite Farm and Ranch Alkyd Semi Gloss F666XX

New Wood, Clapboards, Shingles, Shakes, Trim:

- 1 Coat California CalPro Exterior Oil Primer 23100 or Calpro 100% Acrylic Latex Primer 46100
- 1 or 2 coats FixAll Fix Rite Farm and Ranch Alkyd Semi Gloss F666XX

New Masonry or Cement

Masonry Block, Porous Concrete:

- 1 or 2 coats FixAll Fix Rite Farm and Ranch Alkyd Semi Gloss F666XX

Metal or Wood-Repaint:

- 1 or 2 coats FixAll Fix Rite Farm and Ranch Alkyd Semi Gloss F666XX

Precautions

For exterior use only. Not for use on floors or decks. Nighttime dew settling on wet paint film will slow drying and may flatten the gloss.

Fix-Rite Structure & Farm Exterior Alkyd Paint Semi Gloss - F666 Series

Environmental Health and Safety Information

Fix-Rite Structure & Farm Exterior Alkyd Paint Semi Gloss - F666 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

CAUTION! Combustible Liquid: Keep away from heat and flame. Close container after each use. Use only with adequate ventilation. Wash thoroughly after handling. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. KEEP OUT OF REACH OF CHILDREN.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery, recycling and disposal for regulations.

Place the rags in an empty metal container that has a tight metal lid such as a paint or stain can. Fill the container with water until the rags are submerged; Fill Place the metal lid tightly over the water soaked formerly combustible rags. Place lid tightly on container. Coontact local municipal offices for disposal directions. Never dump solvent down any household or external drains or in any open water.

Notes

Technical Data

Product Type	Finish
Exposure	Exterior
Specular Gloss	50° ±
Volume Solids	57% ± 2
Weight Solids	74% ± 2
Vehicle Solids	
Pigment	
Wet Film Thickness	3.5 - 4.5 mils
Dry Film Thickness	1.5 - 2.0 mils
Viscosity @ 77 °F	88KU ± 5
Max VOC	
Flash Point ° F	Combustible
Thinner	Mineral Spirits
Clean - up	Mineral Spirits

Surface Spread Rate

Smooth	350-400 s.f./gal.
Porous	250-300 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	12 hours
To Handle	24 hours
To Recoat	24 hours
To Wash	7 days

(@ 70 - 77 °F, 50% R.H)

Surface Temperature At Application

Maximum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	China Bristle
Roller	3/8" Nap Synthetic or Natural
Airless Spray	.015 to .018 Tip / 40-60° angles

Available Package Sizes

5 Gallon	Gallon
(Weight Per Gallon:10.46 lbs. ± .5 lb)	

Available Colors and Bases

Available in 5 stock colors