

## Latex Block Filler - F515 Series

### Product Description

This alkali resistant block filler is formulated to fill pores and small voids in masonry and light aggregate block. This ready-mixed Interior/Exterior vinyl acrylic block filler eliminates pin holing and produces a uniform surface texture ready for finish coating.

### Recommended Use

Concrete Block, Porous Masonry and Concrete

### General Surface Preparation

Masonry block should be "bricked down" so that all concrete nibs and projections are removed from the surface. Loose mortar, dirt, dust, grease and oil must also be removed before applying FixAll Block Filler F51500. Large concrete voids or cracks should be patched with an appropriate oil free patching material before painting.

### Application

FixAll Latex Block Filler is supplied ready-to-use but can be thinned sparingly with water if necessary. It can be applied by brush, roller or spray.

Brush - Use a synthetic nylon or polyester brush and apply material generously to the surface. Work the Filler into the masonry until all voids and hairline cracks are filled. Material should be finished brushed in one direction to create an even appearance.

Roller - Use a synthetic or lambs wool 3/8" - 3/4" nap roller cover. Work material into block and finish roll horizontally.

Spray - ProPaint Block Filler is silica free and can be successfully sprayed without doing physical damage to spray equipment. Heavy duty airless units using a .021 to .028 tip are ideal for large scale block filler applications.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Porous Masonry, Block, Concrete:

1 coat FixAll Block Filler F51500

1 or 2 coats FixAll or California® Latex, Alkyd or Oil-modified Urethane in desired finish.

### Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50 °F or when drying conditions are poor. Keep from freezing. Do not use under catalyzed epoxies, epoxy polyesters or aliphatic urethanes.

### Environmental Health and Safety Information

**Keep out of reach of children. Do not take internally. Close container after each use.**

## Latex Block Filler - F515 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Lead Warning !** - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

Technical Data	
<b>Product Type</b>	Primer
<b>Exposure</b>	Interior/ Exterior
<b>Specular Gloss</b>	2° ± 2
<b>Volume Solids</b>	46.7% ± 2
<b>Weight Solids</b>	66.3% ± 2
<b>Vehicle Solids</b>	44.0% ± 2
<b>Pigment</b>	56.0% ± 2
<b>Wet Film Thickness</b>	8.5 mils
<b>Dry Film Thickness</b>	5 mils
<b>Viscosity @ 77 °F</b>	109KU ± 3
<b>Max VOC</b>	100 g/l
<b>Flash Point ° F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water
Surface Spread Rate	
<b>Smooth</b>	200-250 s.f./gal.
<b>Porous</b>	100-150 s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
<b>To Touch</b>	4 hours
<b>To Handle</b>	8 hours
<b>To Recoat</b>	4 hours
<b>To Wash</b>	N/A
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 35°F to Under 100°F	
Tools & Equipments	
<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" -3/4" Nap Synthetic Fiber
<b>Airless Spray</b>	.021 to .028 Tip
Available Package Sizes	
5 Gallon	Gallon
<i>(Weight Per Gallon:13.2 lbs. ± .5 lb)</i>	
Available Colors and Bases	
Available in 0 stock colors	