

Fix-Rite Farm & Ranch Exterior Latex Paint - F608 Series

Product Description

Fix-Rite Farm & Ranch Exterior Latex Paint is a good quality, vinyl / acrylic paint with high covering power. It dries to a uniform low sheen with blister resistant qualities. It is recommended for use on all surfaces where a good quality economical outside paint is desired.

Recommended Use

For use on wood, masonry, metal and aluminum.

General Surface Preparation

Surfaces must be clean and free of surface contaminants. On previously painted surfaces, remove all loose or scaly paint by sanding or scraping so that all remaining paint is tightly adhered to the surface. Fill all of the holes and joints around windows, doors, trim, clapboards and other openings appropriately with exterior Spackle or caulking compound. Spot prime on all bare spots or badly eroded areas with CalPro Latex or Oil Primer. Mildewed areas should be cleaned with an EPA registered mildew solution. For protection use rubber gloves and safety goggles. Rinse with clean water and allow to dry before painting. In areas of excessive chalk, salt or dust, areas should be cleaned with pressure or scrubbed, then rinsed clean. .

Application

FixRite Latex Farm Paint is designed to be applied with a good quality paint applicator. Apply one or two coats to a properly prepared surface. Flow the paint on liberally to assure good hiding and lasting protection. Paint only when surface is above 50° F. Use LATEX FARM PAINT exactly as it comes from the can. If thinning is necessary, use no more than a half pint of water per gallon.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

New Wood, Clapboards, Shingles, Shakes, Trim:
 1 Coat California CalPro Exterior Oil Primer 23100 or Calpro 100% Acrylic Latex Primer 46100
 2 coats FixAll FixRite Acrylic Latex Farm Paint F608XX
 New Stucco, Masonry or Cement Asbestos:
 2 coats FixAll Acrylic Latex Flat Paint F555XX
 Masonry Block, Porous Concrete:
 1 coat FixAll Block Filler F37500
 2 coats FixAll FixRite Acrylic Latex Farm Paint F608XX
 New Galvanized Metal (Downspouts, Facias, Gutters):
 2 coats FixAll FixRite Acrylic Latex Farm Paint F608XX
 Wood-Repaint:
 2 coats FixAll FixRite Acrylic Latex Farm Paint F608XX

Precautions

Do not use when the surface or air temperature is below 50° F.

Environmental Health and Safety Information

Do not take internally. Close container tightly after each use. KEEP AWAY FROM CHILDREN

Fix-Rite Farm & Ranch Exterior Latex Paint - F608 Series

Fix-Rite Farm & Ranch Exterior Latex Paint - F608 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

Technical Data

Product Type	Finish
Exposure	Exterior
Specular Gloss	8° ± 2
Volume Solids	25% ± 2
Weight Solids	42% ± 2
Vehicle Solids	
Pigment	
Wet Film Thickness	5.0 mils
Dry Film Thickness	1.5 mils
Viscosity @ 77 °F	95KU ± 5
Max VOC	100 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	300-400 s.f./gal.
Porous	250-300 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	1 hour
To Handle	8 hours
To Recoat	4 hours
To Wash	14 days

(@ 70 - 77 °F, 50% R.H)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" -3/4" Nap Synthetic Fiber
Airless Spray	.017 to .019 Tip

Available Package Sizes

5 Gallon	Gallon
<i>(Weight Per Gallon:10.7 lbs. ± .5 lb)</i>	

Available Colors and Bases

Available in 3 stock colors