

Latex Block Filler - F515 Series

Product Description

This alkali resistant block filler is formulated to fill pores and small voids in masonry and light aggregate block. This ready-mixed Interior/Exterior vinyl acrylic block filler eliminates pin holing and produces a uniform surface texture ready for finish coating.

Recommended Use

Concrete Block, Porous Masonry and Concrete

General Surface Preparation

Masonry block should be "bricked down" so that all concrete nibs and projections are removed from the surface. Loose mortar, dirt, dust, grease and oil must also be removed before applying FixAll Block Filler F51500. Large concrete voids or cracks should be patched with an appropriate oil free patching material before painting. Concrete and mortar must be cured, generally 30 days, before coating. Moisture content must be 14% or lower, and the pH between 6 and 9.

Application

FixAll Latex Block Filler/Primer is supplied ready-to-use but can be thinned sparingly with water if necessary. It can be applied by brush, roller or spray.

Brush - Use a synthetic nylon or polyester brush and apply material generously to the surface. Work the Filler into the masonry until all voids and hairline cracks are filled. Material should be finished brushed in one direction to create an even appearance.

Roller - Use a synthetic or lambs wool 3/8" - 3/4" nap roller cover. Work material into block and finish roll horizontally.

Spray - ProPaint Block Filler is silica free and can be successfully sprayed without doing physical damage to spray equipment. Heavy duty airless units using a .021 to .028 tip are ideal for large scale block filler applications.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Porous Masonry, Block, Concrete:

1 coat FixAll Latex Block Filler F51500

1 or 2 coats FixAll or California® Latex, Alkyd or Oil-modified Urethane in desired finish.

Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50 °F or when drying conditions are poor. Keep from freezing. Do not use under catalyzed epoxies, epoxy polyesters or aliphatic urethanes.

Environmental Health and Safety Information

Keep out of reach of children. Do not take internally. Close container after each use.
Refer to Safety Data Sheet for additional health and safety information.

Latex Block Filler - F515 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

Technical Data

Product Type	Primer
Exposure	Interior/ Exterior
Specular Gloss	2° ± 2
Volume Solids	46.7% ± 2
Weight Solids	66.3% ± 2
Vehicle Solids	44.0% ± 2
Pigment	56.0% ± 2
Wet Film Thickness	8.5 mils
Dry Film Thickness	5 mils
Viscosity @ 77 °F	109KU ± 3
Max VOC	100 g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water

Surface Spread Rate

Smooth	200-250 s.f./gal.
Porous	100-150 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	4 hours
To Handle	8 hours
To Recoat	4 hours
To Wash	N/A

(@ 70 - 77 °F, 50% R.H)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 35°F to Under 100°F

Tools & Equipments

Brush	Synthetic, Nylon or Polyester
Roller	3/8" -3/4" Nap Synthetic Fiber
Airless Spray	.021 to .028 Tip

Available Package Sizes

5 Gallon	(Weight Per Gallon:13.2 lbs. ± .5 lb)
----------	---------------------------------------

Available Colors and Bases

White	Available in 0 stock colors
-------	-----------------------------