

Spackle Lite - F683 Series

Product Description

A new ready to use wall repair compound based on hollow glass micro-spheres that will not shrink, sag or crack. Fills even large holes and deep cracks in one application. Unlike other lightweight patching compounds, Spackle Lite goes on easily, stays in place, sands easily and can be applied to a feather edge. It may be painted over with latex or oil-based paint when dry.

Recommended Use

For interior use in filling holes, cracks and gouges on wallboard, plaster, wood, stucco and masonry.

General Surface Preparation

Surfaces must be clean, dry and free from dirt, dust, loose plaster, grease, wax, or foreign matter. Roughen smooth surfaces with sand paper.

Application

Stir compound if necessary and apply with a broad putty knife. Spread compound evenly, pressing into holes and cracks, and feathering out the edges. Apply slight excess, overlapping edges of deep cracks and holes. Sand even with surface, using fine sand paper, only after compound has been allowed to dry thoroughly. Primer is recommended for all paints except for Latex Flat. Use recommended primer for the desired finish.

Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

Architectural Specifications

Spackle Lite is designed to fill holes on interior wood metal, plaster wallboard and masonry.
Apply liberally allowing Spackle Lite to exceed the surface imperfection.
Allow to dry, sand and apply a second application.
Allow 1 hour prior to coatings application.

Precautions

Protect against freezing. Do not apply below 45°F. Do not take internally. Close container after each use. Keep out of reach of children.

Environmental Health and Safety Information

Do not take internally. Close container after each use. Keep out of reach of children.

Do not apply to exterior areas if rain or heavy dew is expected. Not recommended in areas subject to high moisture. Do not apply in temperatures below 50°F. Do not use as skim coat on exterior surfaces. Repair is only as good as the substrate it is applied to. Carefully inspect the area to be patched and determine if conditions and product are correct.

Spackle Lite - F683 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

Silica Warning ! - Scraping, sanding or removing old paint or drywall finishing materials from any surface may release lead, asbestos, and/or crystalline silica dust. LEAD, ASBESTOS, AND CRYSTALLINE SILICA ARE TOXIC. For a Guide to Working Safely with Silica", log on to the U.S. Department of Labor's website at: www.osha.gov/dsg/topics/silicacrystalline.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Lead Warning ! - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

Notes

Technical Data	
Product Type	Specialty
Exposure	Interior
Specular Gloss	N/A° ±
Volume Solids	
Weight Solids	
Vehicle Solids	
Pigment	
Wet Film Thickness	
Dry Film Thickness	
Viscosity @ 77 °F	
Max VOC	N/A g/l
Flash Point ° F	Non-Combustible
Thinner	Water
Clean - up	Soap & Water
Surface Spread Rate	
Smooth	N/A s.f./gal.
Porous	N/A s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
To Touch	30 minutes
To Handle	1 hour
To Recoat	1 hour
To Wash	N/A
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 50°F to Under 90°F	
Tools & Equipments	
Brush	
Roller	
Airless Spray	Not Recommended
Available Package Sizes	
1/2 Pint	Gallon
Quart	
<i>(Weight Per Gallon:3.9 lbs. ± .5 lb)</i>	
Available Colors and Bases	
Available in 1 stock colors	