

## WearAll Acrylic Enamel Satin - F528 Series

### Product Description

This durable, easily applied acrylic enamel is designed to provide maximum performance in a satin water-based floor, wall and trim finish. It incorporates color retention, breathability, alkali, water and blister resistance and adhesion into its acrylic formulation.

### Recommended Use

Floors, patios, porches, steps, decks, playrooms, basements, wood, concrete and masonry. Walls and trim where durability and abrasion resistance is required.

### General Surface Preparation

Surface Preparation: Surfaces must be thoroughly cleaned of all dirt and dust. Dirty surfaces should be washed with a strong detergent solution, rinsed with clean water and allowed to dry overnight. Grease, oils and wax be removed by solvent cleaning to insure proper adhesion of the finish paint. All old, loose, scaly or flaking paint must be removed back to a sound substrate before any repainting is attempted. New concrete should be allowed to cure a minimum of 30 days before applying any finish. Steel trowelled, hard or glassy smooth concrete should be mechanically abraded to obtain proper adhesion. Curing agents or concrete hardeners can prevent adhesion of any coating unless the surface is mechanically abraded.

Galvanized Metal should be properly prepared prior to coating. A test patch should be done to ensure proper adhesion.

Wear-All is self-priming over unfinished wood and does not require a wood primer. Wood knots should be spot primed with FixAll Alkyd Stain Killer F20400

### Application

Material is supplied ready to use but can be thinned up to one pint per gallon with water for first coat on new surfaces or for spot-priming bare areas on old finishes.

Please stir well before applying. Avoid brushing back into paint after it has been on the surface for more than five minutes. Allow paint to dry completely before touching up.

PLEASE VERIFY COLOR: All colors should be applied on a small area, allowed to dry and approved for accuracy before painting. The manufacturer or re-seller will not accept liability for unsatisfactory color. All cans should be intermixed and stirred well to achieve continual uniformity.

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Wood, Floors:

2 coats FixAll Wear-All Acrylic Enamel F528XX

Concrete, Patios, Breezeways, Steps:

1 or 2 coats FixAll Wear-All Acrylic Enamel F528XX  
(thin first coat 10-20% with water)

Walls:

2 coats FixAll Wear-All Acrylic Enamel F528XX

Repaint:

1 coat FixAll Wear-All Acrylic Enamel F528XX

Ferrous Metal – Unprimed

1 coat FixAll Fix-Rust Primer F500XX

1-2 coats FixAll Wear-All Acrylic Enamel F528XX

## WearAll Acrylic Enamel Satin - F528 Series

Note: Wear-All Multi-Purpose Acrylic Latex Enamel can be patched and traffic areas relocated with less difficulty than any other floor finish.

### Precautions

Do not add solvents, oils or colors in oil, or mix with other paint types. Do not apply when air or surface temperature is below 50° F or when drying conditions are poor. Keep from freezing. Use adequate ventilation.

Do not use on garage floors. Hot tires or the weight of a vehicle can cause loss of adhesion.

Do not apply over water, glass or other silicate concrete hardeners.

Not recommended on areas utilizing heavy duty lift trucks. Everlife® Urethane Enamel is a better finish for these areas.

### Environmental Health and Safety Information

**Keep out of reach of children. Do not take internally. Close container after each use.**  
**Refer to Safety Data Sheet for additional health and safety information.**

## WearAll Acrylic Enamel Satin - F528 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Lead Warning !** - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Some paint products may contain chemicals which are harmful if they come in contact with exposed skin. Protection for exposed skin (gloves, protective creams) should be available, and used per product directions.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

All floor coatings are more slippery when the surface becomes wet or contaminated by dirt, oils, food, or beverage residues, or other debris. To help reduce the possibility of slipping on a dry, clean floor, add Slip Resistant Additive F09098 before application. To attain the best possible skid resistance, coated areas must be kept dry, properly cleaned and maintained.

FOR PROFESSIONAL USE ONLY.

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

### Technical Data

<b>Product Type</b>	Finish
<b>Exposure</b>	Interior/ Exterior
<b>Specular Gloss</b>	18° ± 4
<b>Volume Solids</b>	31.8% ± 2
<b>Weight Solids</b>	45.4% ± 2
<b>Vehicle Solids</b>	75.3% ± 2
<b>Pigment</b>	24.7% ± 2
<b>Wet Film Thickness</b>	4 mils
<b>Dry Film Thickness</b>	1.2 mils
<b>Viscosity @ 77 °F</b>	95KU ± 5
<b>Max VOC</b>	150 g/l
<b>Flash Point ° F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water

### Surface Spread Rate

<b>Smooth</b>	400-450 s.f./gal.
<b>Porous</b>	275-325 s.f./gal.

(Spray Application is 50% of above)

### Drying Times

<b>To Touch</b>	1 hour
<b>To Handle</b>	16 hours
<b>To Recoat</b>	4 hours
<b>To Wash</b>	14 days

(@ 70 - 77 °F, 50% R.H.)

### Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

### Storage Temperature

Store Between Over 35°F to Under 118°F

### Tools & Equipments

<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" Nap Synthetic Fiber
<b>Airless Spray</b>	.017 to .019 Tip

### Available Package Sizes

5 Gallon	Gallon
(Weight Per Gallon: 10.5 lbs. ± .5 lb)	

### Available Colors and Bases

Pastel Base	Medium Base
Deep Base	Neutral Base
White	

Available in 8 stock colors

## WearAll Acrylic Enamel Satin - F528 Series