

Zone Marking Traffic Paint Alkyd - F935 Series

Product Description

FixAll Alkyd Zone and Traffic Paints are designed for marking traffic lines on streets, highways, parking lots, warehouses and shopping centers. It dries fast and can be applied both interior and exterior to asphalt, concrete, metal and wood surfaces. It hides well and is very durable. Traffic beads may be used with this paint to provide reflective marking.

Recommended Use

For interior and exterior use on asphalt, concrete, metal and wood surfaces.

General Surface Preparation

Surface must be clean, dry and free of dirt, dust, loose paint, oil, grease, wax, rust, bleeding stain and other foreign matter. New concrete should cure 30 days before applying ALKYD ZONE MARKING PAINT. All new asphalt and asphalt sealers should cure one week before being painted. Check asphalt for bleeding by applying a test strip.

Application

For a uniform appearance apply paint in an even thickness. Due to the fast drying properties of this coating, only small areas should be coated using a brush or roller. This paint is best applied by spray. If beads are to be used they should be dropped into wet paint immediately after application at a rate of 6 pounds per gallon of paint.

Method of Application: Brush, roller, marking machine or spray. Non-specialized spray equipment in a wide range of sizes and types can be used.

This product requires no thinning. If thinning is desired, use VM&P Naphtha 659 up to 1/2 pint per gallon.

Clean up

Clean tools and equipment with mineral spirits or turpentine. Do not use water on natural bristle or china bristle brushes.

Architectural Specifications

Concrete, Asphalt, wood and other surfaces requiring a fast drying line marking system;

1 Coat FixAll Alkyd Zone Marking Paint F935xx in desired color.

2 Coats will provide maximum hide and extended longevity.

Precautions

Do not apply when surface or air temperature is below 40° F. Not intended for use as an anti-slip coating.

Environmental Health and Safety Information

Avoid contact with eyes. Do not take internally.

Refer to Safety Data Sheet for additional health and safety information

Zone Marking Traffic Paint Alkyd - F935 Series

*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

CAUTION! FLAMMABLE LIQUID AND VAPOR: Keep away from heat, sparks and flame. Vapors may cause flash fire. Close container after each use. Use only with adequate ventilation. Wash thoroughly after handling. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. **KEEP OUT OF REACH OF CHILDREN.** Working with flammables and combustibles: Fire extinguishers, a safety shower, and fire blankets must be immediately available. Use only explosion-proof electrical equipment, including lighting. Do not leave any material or equipment unattended.

Always use any paint product with proper ventilation. Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below the applicable exposure limit (OSHA PEL) of the components being used. This information is listed on the appropriate Material Safety Data Sheets. All application areas should be ventilated in accordance with applicable OSHA regulations, contact your local office for specific information.

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

USE COMPLETELY OR DISPOSE OF PROPERLY: Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery, recycling and disposal for regulations.

Place the rags in an empty metal container that has a tight metal lid such as a paint or stain can. Fill the container with water until the rags are submerged; Fill Place the metal lid tightly over the water soaked formerly combustible rags. Place lid tightly on container. Contact local municipal offices for disposal directions. Never dump solvent down any household or external drains or in any open water.

Notes

Technical Data

Product Type	Industrial
Exposure	Interior/ Exterior
Specular Gloss	2° ± 2
Volume Solids	50% ± 2
Weight Solids	72% ± 2
Vehicle Solids	
Pigment	
Wet Film Thickness	13 mils
Dry Film Thickness	6 mils
Viscosity @ 77 °F	
Max VOC	450 g/l
Flash Point ° F	Combustible
Thinner	Hi-flash Naphtha
Clean - up	Mineral Spirits

Surface Spread Rate

Smooth	200-250 s.f./gal.
Porous	150-200 s.f./gal.

(Spray Application is 50% of above)

Drying Times

To Touch	15-20 minutes
To Handle	2 hours
To Recoat	2 hours
To Wash	N/A

(@ 70 - 77 °F, 50% R.H)

Surface Temperature At Application

Minimum: Over 50°F	Maximum: Under 90°F
--------------------	---------------------

Storage Temperature

Store Between Over 40°F to Under 90°F

Tools & Equipments

Brush	Bristle
Roller	3/8" - 1/2" Nap
Airless Spray	.017 to .019 Tip, .021 to .028 Tip

Available Package Sizes

5 Gallon	Gallon
(Weight Per Gallon:11.8 lbs. ± .5 lb)	

Available Colors and Bases

White	
Available in 2 stock colors	