

## Zone Marking Traffic Paint Latex - F108 Series

### Product Description

Latex Traffic & Zone Marking Paint is a glare free paint to be used for designating all types of lanes, parking spots and zones. Excellent for exterior use or within factory and commercial environments.

### Recommended Use

Suitable for line marking on pavement zones, lanes, identification of traffic aisles in factories and warehouses or athletic surfaces.

### General Surface Preparation

For zone marking, clean the surface of all dirt, dust, grease, oil or other contaminants. Thin with a small amount of water only if necessary.

### Application

Brush, roller or spray

### Clean up

A mixture of warm water and mild soap is the best cleaning solution for water-based paints. Prepare soapy water and pour into a clean container. Dip the paint brush into the mixture, working the soap through the brush bristles. Follow with a clear water rinse. Repeat the process if necessary. Always use a clean container with clean soapy water and follow with a clear water rinse. For stubborn water-based paints, try mineral spirits or lacquer thinner, followed by warm soapy water and a clear water rinse.

### Architectural Specifications

Coating and re-coating lines or areas on asphalt, concrete, metal or wood surfaces.

1 coat FixAll F108xx Latex Zone and Traffic Paint in desired color.

2 coats can be used to increase hide and extend longevity.

### Precautions

Material should not be thinned with organic solvent. Surface and air temperature should be above 50°F during drying. Do not paint on hot surfaces or in direct sun. Do not apply sooner than 4 hours before heavy dew or rain are expected.

### Environmental Health and Safety Information

**KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN. Do not take internally. Close container after each use.**

## Zone Marking Traffic Paint Latex - F108 Series

\*Depending upon color choice, non zero VOC colorant added to this product may significantly increase VOC levels.

**WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**Lead Warning !** - If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

In an enclosed area and as required, always wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application of any coating unless air monitoring demonstrates that vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

**USE COMPLETELY OR DISPOSE OF PROPERLY:** Dispose of in accordance with applicable Federal, State and Local regulations. Under the Resource Conservation and Recovery Act (RCRA) regulations, it is the responsibility of the product user to determine, at the time of disposal, whether a material should be classified as a hazardous waste. For recycling guidance of any unused amount, contact your local or provincial organization of recovery and recycling. Dry, empty containers may be recycled in a can recycling program where facilities are available and sanctioned by local authorities.

### Notes

Technical Data	
<b>Product Type</b>	Specialty
<b>Exposure</b>	Interior/ Exterior
<b>Specular Gloss</b>	2° ± 2
<b>Volume Solids</b>	34.1% ± 2
<b>Weight Solids</b>	51.0% ± 2
<b>Vehicle Solids</b>	63.0% ± 2
<b>Pigment</b>	37.0% ± 2
<b>Wet Film Thickness</b>	4.5 mils
<b>Dry Film Thickness</b>	1.5 mils
<b>Viscosity @ 77 °F</b>	107KU ± 3
<b>Max VOC</b>	150 g/l
<b>Flash Point ° F</b>	Non-Combustible
<b>Thinner</b>	Water
<b>Clean - up</b>	Soap & Water
Surface Spread Rate	
<b>Smooth</b>	300-350 s.f./gal.
<b>Porous</b>	250-300 s.f./gal.
<i>(Spray Application is 50% of above)</i>	
Drying Times	
<b>To Touch</b>	30 minutes
<b>To Handle</b>	4 hours
<b>To Recoat</b>	2 hours
<b>To Wash</b>	
<i>(@ 70 - 77 °F, 50% R.H)</i>	
Surface Temperature At Application	
Minimum: Over 50°F	Maximum: Under 90°F
Storage Temperature	
Store Between Over 40°F to Under 100°F	
Tools & Equipments	
<b>Brush</b>	Synthetic, Nylon or Polyester
<b>Roller</b>	3/8" - 1/2" Nap
<b>Airless Spray</b>	.017 to .019 Tip
Available Package Sizes	
5 Gallon	Gallon
<i>(Weight Per Gallon:11.25 lbs. ± .5 lb)</i>	
Available Colors and Bases	
White	
Available in 2 stock colors	